

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 21.01.2022

Version number 9 (replaces version 8)

Revision: 20.01.2022

**SECTION 1: Identification of the substance/mixture and of the company/undertaking**

**1.1 Product identifier**

· **Trade name:** DUPLI-COLOR IRON MICA SPRAY various colours

· **Article number:** 707193, 720376, 743740, 743726alt, 743733alt, 743757alt

· **1.2 Relevant identified uses of the substance or mixture and uses advised against**  
No further relevant information available.

· **Sector of Use**

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

· **Product category** PC9a Coatings and paints, thinners, paint removers

· **Process category**

PROC7 Industrial spraying

PROC11 Non industrial spraying

· **Application of the substance / the mixture** Lacquer

**1.3 Details of the supplier of the safety data sheet**

· **Manufacturer/Supplier:**

European Aerosols GmbH\*

Kurt Vogelsang Strasse 6

D-74855 Haßmersheim

Tel.: +49 (0) 6266 750

e-mail: sds-de@european-aerosols.com

\*Formerly known as Motip Dupli GmbH

· **Further information obtainable from:** Department Product Safety

· **1.4 Emergency telephone number:**

Tel.: +49 6266-75-310

Fax +49 6266-75-362

(Mo - Th 08:00 am - 04:00 pm, Fr 08:00 am - 00:30 pm)

UK:

Public emergency phone no: 111

Only for healthcare professionals: 0344 892 0111

Ireland:

Poison center if childs have been poisoned: 01 809 2166 (8:00 am - 10:00 pm, 7 days)

Only for healthcare professionals: 01 809 2566 (24 h / 7 days)

Tox Info Suisse 145 (24-h-emergency number)

**SECTION 2: Hazards identification**

· **2.1 Classification of the substance or mixture**

· **Classification according to Regulation (EC) No 1272/2008**



flame

Aerosol 1

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



health hazard

STOT RE 2

H373

May cause damage to organs through prolonged or repeated exposure.

(Contd. on page 2)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 21.01.2022

Version number 9 (replaces version 8)

Revision: 20.01.2022

**Trade name: DUPLI-COLOR IRON MICA SPRAY various colours**

(Contd. of page 1)



|                   |      |  |
|-------------------|------|--|
| Eye Irrit. 2      | H319 | Causes serious eye irritation.                     |
| STOT SE 3         | H336 | May cause drowsiness or dizziness.                 |
| -----             |      |  |
| Aquatic Chronic 3 | H412 | Harmful to aquatic life with long lasting effects. |

· **2.2 Label elements**

· **Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

· **Hazard pictograms**



GHS02    GHS07    GHS08

· **Signal word** Danger

· **Hazard-determining components of labelling:**

acetone

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclenes, aromatics (2-25%)

Naphtha (petroleum), hydrotreated heavy

1-methoxy-2-propanol

· **Hazard statements**

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

· **Precautionary statements**

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P260 Do not breathe spray.

P280 Wear protective gloves / eye protection.

P284 In case of inadequate ventilation wear respiratory protection.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P312 Call a POISON CENTER/doctor if you feel unwell.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents / container in accordance with regional regulations.

· **Additional information:**

EUH066 Repeated exposure may cause skin dryness or cracking.

Buildup of explosive mixtures possible without sufficient ventilation.

· **2.3 Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

**SECTION 3: Composition/information on ingredients**

· **3.2 Mixtures**

· **Description:** Mixture of substances listed below with nonhazardous additions.

(Contd. on page 3)

GB

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 21.01.2022

Version number 9 (replaces version 8)

Revision: 20.01.2022

**Trade name: DUPLI-COLOR IRON MICA SPRAY various colours**

(Contd. of page 2)

| · <b>Dangerous components:</b>  |   |           |
|---|---|-----------|
| CAS: 67-64-1<br>EINECS: 200-662-2<br>Index number: 606-001-00-8<br>Reg.nr.: 01-2119471330-49  | acetone<br>⚠ Flam. Liq. 2, H225<br>⚠ Eye Irrit. 2, H319; STOT SE 3, H336<br>EUH066  | 20-<25%   |
| CAS: 74-98-6<br>EINECS: 200-827-9<br>Index number: 601-003-00-5<br>Reg.nr.: 01-2119486944-21  | propane<br>⚠ Flam. Gas 1A, H220<br>Press. Gas (Comp.), H280   | 12.5-<20% |
| CAS: 106-97-8<br>EINECS: 203-448-7<br>Index number: 601-004-00-0<br>Reg.nr.: 01-2119474691-32 | butane (containing < 0,1 % butadiene (203-450-8))<br>⚠ Flam. Gas 1A, H220<br>Press. Gas (Comp.), H280   | 5-<10%    |
| EC number: 919-857-5<br>Reg.nr.: 01-2119463258-33   | Naphtha (petroleum), hydrotreated heavy<br>⚠ Flam. Liq. 3, H226<br>⚠ Asp. Tox. 1, H304<br>⚠ STOT SE 3, H336   | 5-<10%    |
| CAS: 107-98-2<br>EINECS: 203-539-1<br>Index number: 603-064-00-3<br>Reg.nr.: 01-2119457435-35 | 1-methoxy-2-propanol<br>⚠ Flam. Liq. 3, H226<br>⚠ STOT SE 3, H336   | 2.5-<5%   |
| CAS: 75-28-5<br>EINECS: 200-857-2<br>Index number: 601-004-00-0<br>Reg.nr.: 01-2119485395-27  | isobutane (containing < 0,1 % butadiene (203-450-8))<br>⚠ Flam. Gas 1A, H220<br>Press. Gas (Comp.), H280  | 2.5-<5%   |
| CAS: 108-65-6<br>EINECS: 203-603-9<br>Index number: 607-195-00-7<br>Reg.nr.: 01-2119475791-29 | 2-methoxy-1-methylethyl acetate<br>⚠ Flam. Liq. 3, H226<br>⚠ STOT SE 3, H336  | <2.5%     |
| CAS: 123-86-4<br>EINECS: 204-658-1<br>Index number: 607-025-00-1<br>Reg.nr.: 01-2119485493-29 | n-butyl acetate<br>⚠ Flam. Liq. 3, H226<br>⚠ STOT SE 3, H336<br>EUH066  | <2.5%     |
| EC number: 905-588-0<br>Index number: 601-022-00-9<br>Reg.nr.: 01-2119488216-32               | xylene<br>⚠ Flam. Liq. 3, H226<br>⚠ STOT RE 2, H373; Asp. Tox. 1, H304<br>⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315;<br>Eye Irrit. 2, H319; STOT SE 3, H335           | <2.5%     |
| EC number: 919-446-0<br>Index number: 649-330-00-2<br>Reg.nr.: 01-2119458049-33               | Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)<br>⚠ Flam. Liq. 3, H226<br>⚠ STOT RE 1, H372; Asp. Tox. 1, H304<br>⚠ Aquatic Chronic 2, H411<br>⚠ STOT SE 3, H336 | <2.5%     |
| EC number: 918-481-9<br>Reg.nr.: 01-2119457273-39   | Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics<br>⚠ Acute Tox. 3, H331<br>⚠ Asp. Tox. 1, H304  | <2.5%     |

(Contd. on page 4)

GB

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 21.01.2022

Version number 9 (replaces version 8)

Revision: 20.01.2022

**Trade name: DUPLI-COLOR IRON MICA SPRAY various colours**

(Contd. of page 3)

|   |   |       |
|---|---|-------|
| EC number: 918-668-5<br>Reg.nr.: 01-2119455851-35   | Hydrocarbons, C9, aromatics<br>Flam. Liq. 3, H226<br>Asp. Tox. 1, H304<br>Aquatic Chronic 2, H411<br>STOT SE 3, H335-H336<br>EUH066   | <2.5% |
| CAS: 149-57-5<br>EINECS: 205-743-6<br>Index number: 607-230-00-6<br>Reg.nr.: 01-2119488942-23 | 2-ethylhexanoic acid<br>Repr. 2, H361d  | ≤0.5% |
| CAS: 22464-99-9<br>EINECS: 245-018-1<br>Reg.nr.: 01-2119979088-21                             | Zirkonium 2-ethylhexanoat<br>Repr. 2, H361  | ≤0.5% |
| EC number: 939-607-9  | Quaternary ammonium compounds, C12-14 (even-numbered)-alkylethyldimethyl, ethyl sulphates<br>Acute Tox. 3, H311<br>Skin Corr. 1C, H314; Eye Dam. 1, H318<br>Aquatic Acute 1, H400 (M=10); Aquatic Chronic 1, H410 (M=1)<br>Acute Tox. 4, H302 | ≤0.5% |

· **Additional information:**

The content of Benzene (EINECS-Nr. 200-753-7) in the ingredients is less than 0,1% (Note P Annex IA 1272/2008 EU), so the classification as carcinogen need not to apply.

xylene: Contains ethylbenzene CAS 100-41-4

For the wording of the listed hazard phrases refer to section 16.

**SECTION 4: First aid measures**

· **4.1 Description of first aid measures**

· **General information:**

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· **After inhalation:** Supply fresh air; consult doctor in case of complaints.

· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

· **After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· **After swallowing:** Drink plenty of water and provide fresh air. Call for a doctor immediately.

· **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.

· **4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

**SECTION 5: Firefighting measures**

· **5.1 Extinguishing media**

· **Suitable extinguishing agents:**

CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

Use fire extinguishing methods suitable to surrounding conditions.

· **5.2 Special hazards arising from the substance or mixture**

During heating or in case of fire poisonous gases are produced.

· **5.3 Advice for firefighters -**

· **Protective equipment:**

Wear self-contained respiratory protective device.

Do not inhale explosion gases or combustion gases.

(Contd. on page 5)

GB

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 21.01.2022

Version number 9 (replaces version 8)

Revision: 20.01.2022

**Trade name: DUPLI-COLOR IRON MICA SPRAY various colours**

Mouth respiratory protective device.

(Contd. of page 4)

**SECTION 6: Accidental release measures**

**· 6.1 Personal precautions, protective equipment and emergency procedures**

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

Keep away from ignition sources.

**· 6.2 Environmental precautions:**

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

**· 6.3 Methods and material for containment and cleaning up:**

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

**· 6.4 Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

**SECTION 7: Handling and storage**

**· 7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace.

**· Information about fire - and explosion protection:**

Keep ignition sources away - Do not smoke.

Keep respiratory protective device available.

**· 7.2 Conditions for safe storage, including any incompatibilities**

**· Storage:**

**· Requirements to be met by storerooms and receptacles:**

Observe official regulations on storing packagings with pressurised containers.

**· Information about storage in one common storage facility:** Not required.

**· Further information about storage conditions:** Keep container tightly sealed.

**· Storage class:** 2 B

**· 7.3 Specific end use(s)** No further relevant information available.

**SECTION 8: Exposure controls/personal protection**

**· 8.1 Control parameters**

**· Ingredients with limit values that require monitoring at the workplace:**

**67-64-1 acetone**

WEL Short-term value: 3620 mg/m<sup>3</sup>, 1500 ppm

Long-term value: 1210 mg/m<sup>3</sup>, 500 ppm

**106-97-8 butane (containing < 0,1 % butadiene (203-450-8))**

WEL Short-term value: 1810 mg/m<sup>3</sup>, 750 ppm

Long-term value: 1450 mg/m<sup>3</sup>, 600 ppm

Carc (if more than 0.1% of buta-1.3-diene)

**107-98-2 1-methoxy-2-propanol**

WEL Short-term value: 560 mg/m<sup>3</sup>, 150 ppm

Long-term value: 375 mg/m<sup>3</sup>, 100 ppm

Sk

**108-65-6 2-methoxy-1-methylethyl acetate**

WEL Short-term value: 548 mg/m<sup>3</sup>, 100 ppm

Long-term value: 274 mg/m<sup>3</sup>, 50 ppm

Sk

(Contd. on page 6)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 21.01.2022

Version number 9 (replaces version 8)

Revision: 20.01.2022

Trade name: **DUPLI-COLOR IRON MICA SPRAY various colours**

(Contd. of page 5)

**123-86-4 n-butyl acetate**

WEL Short-term value: 966 mg/m<sup>3</sup>, 200 ppm  
Long-term value: 724 mg/m<sup>3</sup>, 150 ppm

**xylene**

WEL Short-term value: 441 mg/m<sup>3</sup>, 100 ppm  
Long-term value: 220 mg/m<sup>3</sup>, 50 ppm  
Sk; BMGV

· **Ingredients with biological limit values:****xylene**

BMGV 650 mmol/mol creatinine  
Medium: urine  
Sampling time: post shift  
Parameter: methyl hippuric acid

· **Additional information:** The lists valid during the making were used as basis.· **8.2 Exposure controls**

- **Appropriate engineering controls** No further data; see item 7.
- **Individual protection measures, such as personal protective equipment**
- **General protective and hygienic measures:**  
Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing  
Wash hands before breaks and at the end of work.  
Store protective clothing separately.  
Do not inhale gases / fumes / aerosols.  
Avoid contact with the eyes and skin.  
Avoid contact with the eyes.

· **Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Filter A2/P3

· **Hand protection**

Protective gloves

· **Material of gloves**

Butyl rubber, BR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· **Penetration time of glove material**

Butyl rubber gloves with a thickness of 0.4 mm are resistant to:

Acetone: 480 min

Butyl acetate: 60 min

Ethyl acetate: 170 min

Xylene: 42 min

Butyl rubber gloves with a thickness of 0.4 mm are solvent resistant for 42- 480 minutes. As protective measure, we recommend that users and responsible persons for work safety assume solvent resistance length of 42 minutes. Considering the data in section 3 of this SDS, one can assume longer resistance length in particular cases.

(Contd. on page 7)

**Trade name: DUPLI-COLOR IRON MICA SPRAY various colours**

(Contd. of page 6)

· **Eye/face protection**



Tightly sealed goggles

**SECTION 9: Physical and chemical properties**

· **9.1 Information on basic physical and chemical properties**

· **General Information**

|   |                                     |
|---|-------------------------------------|
| · <b>Physical state</b>   | Aerosol                             |
| · <b>Colour:</b>  | According to product specification  |
| · <b>Odour:</b>   | Characteristic                      |
| · <b>Odour threshold:</b>   | Not determined.                     |
| · <b>Melting point/freezing point:</b>                            | Undetermined.                       |
| · <b>Boiling point or initial boiling point and boiling range</b> | Not applicable, as aerosol.         |
| · <b>Flammability</b>   | Not applicable.                     |
| · <b>Lower and upper explosion limit</b>                          |                                     |
| · <b>Lower:</b>   | 1.7 Vol %                           |
| · <b>Upper:</b>   | 13 Vol %                            |
| · <b>Flash point:</b>   | Not applicable, as aerosol.         |
| · <b>Decomposition temperature:</b>                               | Not determined.                     |
| · <b>pH</b>   | Not determined.                     |
| · <b>Viscosity:</b>   |                                     |
| · <b>Kinematic viscosity</b>                                      | Not determined.                     |
| · <b>Dynamic:</b>   | Not determined.                     |
| · <b>Solubility</b>   |                                     |
| · <b>water:</b>   | Not miscible or difficult to mix.   |
| · <b>Partition coefficient n-octanol/water (log value)</b>        | Not determined.                     |
| · <b>Vapour pressure at 20 °C (68 °F):</b>                        | 8300 hPa (6225.5 mm Hg)             |
| · <b>Density and/or relative density</b>                          |                                     |
| · <b>Density at 20 °C (68 °F):</b>                                | 0.9 g/cm <sup>3</sup> (7.5 lbs/gal) |
| · <b>Relative density</b>   | Not determined.                     |
| · <b>Vapour density</b>   | Not determined.                     |

· **9.2 Other information**

|  |                 |
|--|-----------------|
| · <b>Appearance:</b>   |                 |
| · <b>Form:</b>   | Aerosol         |
| · <b>Important information on protection of health and environment, and on safety.</b> |                 |
| · <b>Ignition temperature:</b>   | 365 °C (689 °F) |
| · <b>Explosive properties:</b>   | Not determined. |
| · <b>Solvent content:</b>  |                 |
| · <b>Organic solvents:</b>   | 69.7 %          |
| · <b>VOC (EC)</b>  | ---             |
|  | 627.7 g/l       |
| · <b>VOC-EU%</b>   | 69.74 %         |
| · <b>Solids content:</b>   | 15.9 %          |
| · <b>Change in condition</b>   |                 |
| · <b>Evaporation rate</b>  | Not applicable. |

· **Information with regard to physical hazard classes**

|                          |   |
|--------------------------|---|
| · <b>Explosives</b>      | Void  |
| · <b>Flammable gases</b> | Void  |
| · <b>Aerosols</b>        | Extremely flammable aerosol. Pressurised container:<br>May burst if heated. |

(Contd. on page 8)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 21.01.2022

Version number 9 (replaces version 8)

Revision: 20.01.2022

Trade name: **DUPLI-COLOR IRON MICA SPRAY various colours**

(Contd. of page 7)

|  |      |
|--|------|
| · <b>Oxidising gases</b>   | Void |
| · <b>Gases under pressure</b>  | Void |
| · <b>Flammable liquids</b>   | Void |
| · <b>Flammable solids</b>  | Void |
| · <b>Self-reactive substances and mixtures</b>                                     | Void |
| · <b>Pyrophoric liquids</b>  | Void |
| · <b>Pyrophoric solids</b>   | Void |
| · <b>Self-heating substances and mixtures</b>                                      | Void |
| · <b>Substances and mixtures, which emit flammable gases in contact with water</b> | Void |
| · <b>Oxidising liquids</b>   | Void |
| · <b>Oxidising solids</b>  | Void |
| · <b>Organic peroxides</b>   | Void |
| · <b>Corrosive to metals</b>   | Void |
| · <b>Desensitised explosives</b>   | Void |

### SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

### SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity**

· **LD/LC50 values relevant for classification:**

#### 67-64-1 acetone

|            |           |                       |
|------------|-----------|-----------------------|
| Oral       | LD50      | 5800 mg/kg (rat)      |
| Dermal     | LD50      | >15800 mg/kg (rabbit) |
| Inhalative | LC50 / 4h | 76 mg/l (rat)         |

#### 108-65-6 2-methoxy-1-methylethyl acetate

|            |            |                      |
|------------|------------|----------------------|
| Oral       | LD50       | 8530 mg/kg (rat)     |
| Dermal     | LD50       | >5000 mg/kg (rabbit) |
| Inhalative | LC50 / 4 h | >10000 mg/m3 (rat)   |

#### 123-86-4 n-butyl acetate

|            |            |                              |
|------------|------------|------------------------------|
| Oral       | LD50       | 10800 mg/kg (rat) (OECD 401) |
| Dermal     | LD50       | >17600 mg/kg (rabbit)        |
| Inhalative | LC50 / 4 h | >21 mg/m3 (rat)              |

#### xylene

|            |            |                     |
|------------|------------|---------------------|
| Oral       | LD50       | 3523 mg/kg (rat)    |
| Dermal     | LD50       | 2000 mg/kg (rabbit) |
| Inhalative | LC50 / 4 h | 29000 mg/m3 (rat)   |

#### Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

|        |      |                    |
|--------|------|--------------------|
| Oral   | LD50 | >15000 mg/kg (rat) |
| Dermal | LD50 | >3400 mg/kg (rat)  |

(Contd. on page 9)



**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 21.01.2022

Version number 9 (replaces version 8)

Revision: 20.01.2022

**Trade name: DUPLI-COLOR IRON MICA SPRAY various colours**

(Contd. of page 8)

|  |             |                                |
|--|-------------|--------------------------------|
| Inhalative   | LC50 / 4 h  | 8200 mg/m <sup>3</sup> (rat)   |
|  | LC50 / 48 h | 16 mg/l (daphnia magna)        |
| <b>Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, &lt; 2% aromatics</b>                  |             |                                |
| Oral   | LD50        | >5000 mg/kg (rat) (OECD 401)   |
| Dermal   | LD50        | 3160 mg/kg (rabbit) (OECD 402) |
| Inhalative   | LC50 / 4h   | 6.1 mg/l (rat) (OECD 403)      |
| <b>Hydrocarbons, C9, aromatics</b>   |             |                                |
| Oral   | LD50        | 3592 mg/kg (rat)               |
| Dermal   | LD50        | 3160 mg/kg (rabbit)            |
| <b>149-57-5 2-ethylhexanoic acid</b>   |             |                                |
| Oral   | LD50        | 2043 mg/kg (rat)               |
| Dermal   | LD50        | >2000 mg/kg (rat)              |
| <b>Quaternary ammonium compounds, C12-14 (even-numbered)-alkylethyldimethyl, ethyl sulphates</b> |             |                                |
|  | LC50 / 96 h | 13.8 mg/l (fish)               |

- **Skin corrosion/irritation** No irritant effect.
- **Serious eye damage/irritation** Causes serious eye irritation.
- **Respiratory or skin sensitisation** No sensitising effects known.
- **STOT-single exposure** May cause drowsiness or dizziness.
- **STOT-repeated exposure** May cause damage to organs through prolonged or repeated exposure.
- **11.2 Information on other hazards**

- **Endocrine disrupting properties**

None of the ingredients is listed.

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Aquatic toxicity:

##### 67-64-1 acetone

|             |                                     |
|-------------|-------------------------------------|
| LC50/96h    | 8300 mg/l (fish)                    |
| EC50/96h    | 7200 mg/l (algae)                   |
| LC50 / 48 h | 8450 mg/l (crustacean (water flea)) |

##### 108-65-6 2-methoxy-1-methylethyl acetate

|             |  |
|-------------|--|
| EC50 / 48 h | >500 mg/l (daphnia magna)                              |
| LC50 / 96 h | 100-180 mg/l (oncorhynchus mykiss / Regenbogenforelle) |

##### xylene

|             |                          |
|-------------|--------------------------|
| EC50 / 48 h | 7.4 mg/l (daphnia magna) |
| LC50 / 96 h | 13.5 mg/l (fish)         |

##### Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

|             |  |
|-------------|--|
| LC50 / 72 h | 7 mg/l (Pseudokirchneriella Subcapitata) |
| LC50 / 96 h | 20 mg/l (Regenbogenforelle)              |

##### Hydrocarbons, C9, aromatics

|             |   |
|-------------|---|
| EC50 / 48 h | 3.2 mg/l (Daphnia magna)                    |
| EC50 / 72 h | 2.75 mg/l (Pseudokirchneriella Subcapitata) |
| EC50 / 96 h | 9.2 mg/l (Regenbogenforelle)                |

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.

(Contd. on page 10)

GB

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 21.01.2022

Version number 9 (replaces version 8)

Revision: 20.01.2022

Trade name: **DUPLI-COLOR IRON MICA SPRAY** various colours

(Contd. of page 9)

· **12.5 Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

· **12.6 Endocrine disrupting properties**

The product does not contain substances with endocrine disrupting properties.

· **12.7 Other adverse effects**

· **Remark:** Harmful to fish

· **Additional ecological information:**

· **General notes:**

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

**SECTION 13: Disposal considerations**

· **13.1 Waste treatment methods**

· **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· **Uncleaned packaging:**

· **Recommendation:**

Dispose of packaging according to regulations on the disposal of packagings.

Non contaminated packagings may be recycled.

**SECTION 14: Transport information**

· **14.1 UN number or ID number**

· **ADR, IMDG, IATA**

UN1950

· **14.2 UN proper shipping name**

· **ADR**

1950 AEROSOLS

· **IMDG**

AEROSOLS

· **IATA**

AEROSOLS, flammable

· **14.3 Transport hazard class(es)**

· **ADR**



· **Class**

2 5F Gases.

· **Label**

2.1

· **IMDG, IATA**



· **Class**

2.1 Gases.

· **Label**

2.1

· **14.4 Packing group**

· **ADR, IMDG, IATA**

not regulated

· **14.5 Environmental hazards:**

Not applicable.

· **14.6 Special precautions for user**

Warning: Gases.

(Contd. on page 11)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 21.01.2022

Version number 9 (replaces version 8)

Revision: 20.01.2022

Trade name: **DUPLI-COLOR IRON MICA SPRAY various colours**

(Contd. of page 10)

|   |   |
|---|---|
| · <b>Hazard identification number (Kemler code):</b>                  | -   |
| · <b>EMS Number:</b>  | F-D,S-U   |
| · <b>Stowage Code</b>   | SW1 Protected from sources of heat.<br>SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.  |
| · <b>Segregation Code</b>   | SG69 For AEROSOLS with a maximum capacity of 1 litre:<br>Segregation as for class 9. Stow "separated from" class 1 except for division 1.4.<br>For AEROSOLS with a capacity above 1 litre:<br>Segregation as for the appropriate subdivision of class 2.<br>For WASTE AEROSOLS:<br>Segregation as for the appropriate subdivision of class 2. |
| · <b>14.7 Maritime transport in bulk according to IMO instruments</b> | Not applicable.   |
| · <b>Transport/Additional information:</b>                            |   |
| · <b>ADR</b>  |   |
| · <b>Limited quantities (LQ)</b>                                      | 1L  |
| · <b>Excepted quantities (EQ)</b>                                     | Code: E0<br>Not permitted as Excepted Quantity  |
| · <b>Transport category</b>   | 2   |
| · <b>Tunnel restriction code</b>                                      | D   |
| · <b>IMDG</b>   |   |
| · <b>Limited quantities (LQ)</b>                                      | 1L  |
| · <b>Excepted quantities (EQ)</b>                                     | Code: E0<br>Not permitted as Excepted Quantity  |
| · <b>UN "Model Regulation":</b>                                       | UN 1950 AEROSOLS, 2.1   |

\* **SECTION 15: Regulatory information**

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category P3a** FLAMMABLE AEROSOLS
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 150 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t
- **National regulations:**
- **Information about limitation of use:**
- **Substances of very high concern (SVHC) according to REACH, Article 57**
- None of the ingredients is listed.
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

\* **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**
- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.

(Contd. on page 12)

**Safety data sheet**  
according to 1907/2006/EC, Article 31

Printing date 21.01.2022

Version number 9 (replaces version 8)

Revision: 20.01.2022

**Trade name: DUPLI-COLOR IRON MICA SPRAY various colours**

(Contd. of page 11)

- H226 *Flammable liquid and vapour.*  
 H280 *Contains gas under pressure; may explode if heated.*  
 H302 *Harmful if swallowed.*  
 H304 *May be fatal if swallowed and enters airways.*  
 H311 *Toxic in contact with skin.*  
 H312 *Harmful in contact with skin.*  
 H314 *Causes severe skin burns and eye damage.*  
 H315 *Causes skin irritation.*  
 H318 *Causes serious eye damage.*  
 H319 *Causes serious eye irritation.*  
 H331 *Toxic if inhaled.*  
 H332 *Harmful if inhaled.*  
 H335 *May cause respiratory irritation.*  
 H336 *May cause drowsiness or dizziness.*  
 H361 *Suspected of damaging fertility or the unborn child.*  
 H361d *Suspected of damaging the unborn child.*  
 H372 *Causes damage to organs through prolonged or repeated exposure.*  
 H373 *May cause damage to organs through prolonged or repeated exposure.*  
 H400 *Very toxic to aquatic life.*  
 H410 *Very toxic to aquatic life with long lasting effects.*  
 H411 *Toxic to aquatic life with long lasting effects.*  
 EUH066 *Repeated exposure may cause skin dryness or cracking.*

**Abbreviations and acronyms:**

- RID: *Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)*  
 IATA-DGR: *Dangerous Goods Regulations by the "International Air Transport Association" (IATA)*  
 ICAO: *International Civil Aviation Organisation*  
 ADR: *Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)*  
 IMDG: *International Maritime Code for Dangerous Goods*  
 IATA: *International Air Transport Association*  
 GHS: *Globally Harmonised System of Classification and Labelling of Chemicals*  
 EINECS: *European Inventory of Existing Commercial Chemical Substances*  
 ELINCS: *European List of Notified Chemical Substances*  
 CAS: *Chemical Abstracts Service (division of the American Chemical Society)*  
 VOC: *Volatile Organic Compounds (USA, EU)*  
 LC50: *Lethal concentration, 50 percent*  
 LD50: *Lethal dose, 50 percent*  
 PBT: *Persistent, Bioaccumulative and Toxic*  
 SVHC: *Substances of Very High Concern*  
 vPvB: *very Persistent and very Bioaccumulative*  
 Flam. Gas 1A: *Flammable gases – Category 1A*  
 Aerosol 1: *Aerosols – Category 1*  
 Press. Gas (Comp.): *Gases under pressure – Compressed gas*  
 Flam. Liq. 2: *Flammable liquids – Category 2*  
 Flam. Liq. 3: *Flammable liquids – Category 3*  
 Acute Tox. 4: *Acute toxicity – Category 4*  
 Acute Tox. 3: *Acute toxicity – Category 3*  
 Skin Corr. 1C: *Skin corrosion/irritation – Category 1C*  
 Skin Irrit. 2: *Skin corrosion/irritation – Category 2*  
 Eye Dam. 1: *Serious eye damage/eye irritation – Category 1*  
 Eye Irrit. 2: *Serious eye damage/eye irritation – Category 2*  
 Repr. 2: *Reproductive toxicity – Category 2*  
 Repr. 2: *Reproductive toxicity – Category 2*  
 STOT SE 3: *Specific target organ toxicity (single exposure) – Category 3*  
 STOT RE 1: *Specific target organ toxicity (repeated exposure) – Category 1*  
 STOT RE 2: *Specific target organ toxicity (repeated exposure) – Category 2*  
 Asp. Tox. 1: *Aspiration hazard – Category 1*  
 Aquatic Acute 1: *Hazardous to the aquatic environment - acute aquatic hazard – Category 1*  
 Aquatic Chronic 1: *Hazardous to the aquatic environment - long-term aquatic hazard – Category 1*  
 Aquatic Chronic 2: *Hazardous to the aquatic environment - long-term aquatic hazard – Category 2*  
 Aquatic Chronic 3: *Hazardous to the aquatic environment - long-term aquatic hazard – Category 3*

**\* Data compared to the previous version altered.**