

Page 1/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 21.06.2022 Version number 9 (replaces version 8) Revision: 20.06.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: DUPLI-COLOR TUNING MAGIC LIGHTS Toch-up-pencil all colours
- · Article number: 668821, 668838, 668944, 668951
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Sector of Use

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

- · Product category PC9a Coatings and paints, thinners, paint removers
- · Process category PROC10 Roller application or brushing
- · Application of the substance / the mixture Paint
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

European Aerosols GmbH* Kurt Vogelsang Strasse 6 D-74855 Haßmersheim

Tel.: +49 (0) 6266 750

e-mail: sds-de@european-aerosols.com

*Formerly known as Motip Dupli GmbH

- · Further information obtainable from: Department Product Safety
- · 1.4 Emergency telephone number:

Tel.:+49 6266-75-310

Fax +49 6266-75-362

(Mo - Th 08:00 am - 04:00 pm, Fr 08:00 am - 00:30 pm)

UK:

Public emergeny phone no: 111

Only for healthcare professionals: 0344 892 0111

Ireland:

Poison center if childs have been poisened: 01 809 2166 (8:00 am - 10:00 pm, 7 days)

Only for healthcare professionals: 01 809 2566 (24 h / 7 days)

Tox Info Suisse 145 (24-h-emergency number)

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



Flam. Liq. 3 H226 Flammable liquid and vapour.



STOT SE 3 H336 May cause drowsiness or dizziness.

(Contd. on page 2)

Printing date 21.06.2022 Version number 9 (replaces version 8) Revision: 20.06.2022

Trade name: DUPLI-COLOR TUNING MAGIC LIGHTS Toch-up-pencil all colours

(Contd. of page 1)

· 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

· Hazard pictograms





GHS02

· Signal word Warning

· Hazard-determining components of labelling:

n-butyl acetate

2-methoxy-1-methylethyl acetate

· Hazard statements

H226 Flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P260 Do not breathe vapours.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P403 Store in a well-ventilated place.

P501 Dispose of contents / container in accordance with regional regulations.

· Additional information:

In container sizes up to 125ml the labelling can be reduced in accordance with Article 29 (2) in connection with Annex I No. 1.5.2.

EUH066 Repeated exposure may cause skin dryness or cracking.

EUH208 Contains [N,N,N',N',N'',N''-hexaethyl-29H,31H-phthalocyaninetrimethylaminato(2-)-N29,N30,N31,N32]copper. May produce an allergic reaction.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:			
CAS: 123-86-4	CAS: 123-86-4 n-butyl acetate		
EINECS: 204-658-1	ⓑ Flam. Liq. 3, H226		
Index number: 607-025-00-1			
Reg.nr.: 01-2119485493-29	EUH066		
CAS: 9004-70-0	cellulose nitrate	10-<12.5%	
	♦ Expl. 1.1, H201		
CAS: 108-65-6	2-methoxy-1-methylethyl acetate	5-<10%	
EINECS: 203-603-9	<u></u> ♦ Flam. Liq. 3, H226		
Index number: 607-195-00-7	♦ STOT SE 3, H336		
Reg.nr.: 01-2119475791-29			
EC number: 905-588-0	xylene	5-<10%	
Index number: 601-022-00-9	7 1 tum. Etg. 5, 11220		
Reg.nr.: 01-2119488216-32	🕉 STOT RÊ 2, H373; Asp. Tox. 1, H304		
	Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315;		
	Eye Irrit. 2, H319; STOT SE 3, H335		
		Contd on page 3	

(Contd. on page 3)

Printing date 21.06.2022 Version number 9 (replaces version 8) Revision: 20.06.2022

Trade name: DUPLI-COLOR TUNING MAGIC LIGHTS Toch-up-pencil all colours

		Contd. of page 2)
CAS: 64-17-5	ethanol	2.5-<5%
EINECS: 200-578-6	♦ Flam. Liq. 2, H225	
Index number: 603-002-00-5		
Reg.nr.: 01-2119457610-43	Specific concentration limit: Eye Irrit. 2; H319: C ≥ 50 %	
CAS: 147-14-8	phthalocyanine blue	2.5-<5%
EINECS: 205-685-1	substance with a Community workplace exposure limit	
Reg.nr.: 2119458771-32		
CAS: 28654-73-1	[N,N,N',N',N'',N''-hexaethyl-29H,31H-	≤ 0.5%
EINECS: 249-125-4	phthalocyaninetrimethylaminato(2-)-N29,N30,N31,N32]copper	
Reg.nr.: 01-2119971074-38	💠 Skin Sens. 1B, H317	

· Additional information:

The content of Benzene (EINECS-Nr. 200-753-7) in the ingredients is less than 0,1% (Note P Annex 1A 1272/2008 EU), so the classification as carcinogen need not to apply.

xylene: Contains ethylbenzene CAS 100-41-4

CAS 9004-70-0: GB CLP Note T

For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

- · 5.3 Advice for firefighters -
- · Protective equipment: Mouth respiratory protective device.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

Keep away from ignition sources.

- · 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

(Contd. on page 4)

Printing date 21.06.2022 Version number 9 (replaces version 8) Revision: 20.06.2022

Trade name: DUPLI-COLOR TUNING MAGIC LIGHTS Toch-up-pencil all colours

(Contd. of page 3)

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Use only in well ventilated areas.

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage.
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 3
- \cdot 7.3 *Specific end use*(s) *No further relevant information available.*

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

. Ingradiants with	limit values that	t reauire monitoring	at the workplace
· Ingreatents with	unu values mai	. TEUMITE MUMILUM MY	ul lile will killuce.

123-86-4 n-butyl acetate

WEL Short-term value: 966 mg/m³, 200 ppm Long-term value: 724 mg/m³, 150 ppm

108-65-6 2-methoxy-1-methylethyl acetate

WEL Short-term value: 548 mg/m³, 100 ppm Long-term value: 274 mg/m³, 50 ppm

SK

xylene

WEL Short-term value: 441 mg/m³, 100 ppm Long-term value: 220 mg/m³, 50 ppm

Sk; BMGV

64-17-5 ethanol

WEL Long-term value: 1920 mg/m³, 1000 ppm

147-14-8 phthalocyanine blue

WEL Short-term value: 2 mg/m³
Long-term value: 1 mg/m³
dusts and mists, as Cu

· Ingredients with biological limit values:

xylene

BMGV 650 mmol/mol creatinine

Medium: urine

Sampling time: post shift Parameter: methyl hippuric acid

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see item 7.

(Contd. on page 5)

Printing date 21.06.2022 Version number 9 (replaces version 8) Revision: 20.06.2022

Trade name: DUPLI-COLOR TUNING MAGIC LIGHTS Toch-up-pencil all colours

(Contd. of page 4)

- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

· Respiratory protection:



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Filter A2/P3

- · Hand protection Not required.
- · Material of gloves Not required.
- · Penetration time of glove material Not required.
- · Eye/face protection



Tightly sealed goggles

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Physical state Fluid

· Colour: According to product specification

Odour: Characteristic
 Odour threshold: Not determined.
 Melting point/freezing point: Undetermined.

· Boiling point or initial boiling point and boiling

range 78 °C (172.4 °F)
⋅ Flammability Flammable.

· Lower and upper explosion limit

Lower: 1.2 Vol % (123-86-4 n-butyl acetate)
 ∙ Upper: 15 Vol % (9004-70-0 cellulose nitrate)

Flash point: 27 °C (80.6 °F)
 Ignition temperature: 180 °C (356 °F)
 Decomposition temperature: Not determined.

• pH Mixture is non-soluble (in water).

· Viscosity:

• Kinematic viscosity at 20 °C (68 °F) 90 s (ISO 4 mm) • Dynamic: Not determined.

· Solubility

• water: Not miscible or difficult to mix.

· Partition coefficient n-octanol/water (log value) Not determined.

• Vapour pressure at 20 °C (68 °F): 58.7 hPa (44 mm Hg) (9004-70-0 cellulose nitrate)

· Density and/or relative density

Density at 20 °C (68 °F):
 Relative density
 Vapour density
 Not determined.
 Not determined.

· 9.2 Other information

· Appearance:

· Form: Fluid

(Contd. on page 6)

Printing date 21.06.2022 Version number 9 (replaces version 8) Revision: 20.06.2022

65.4 %

653.7 g/l

Trade name: DUPLI-COLOR TUNING MAGIC LIGHTS Toch-up-pencil all colours

(Contd. of page 5)

· Important information on protection of health and

environment, and on safety. • Explosive properties:

Product is not explosive. However, formation of

explosive air/vapour mixtures are possible.

· Solvent content:

· Organic solvents: · VOC (EC)

· VOC-EU% 65.37 % *· Solids content:* 32.2 %

· Change in condition

· Evaporation rate Not determined.

· Information with regard to physical hazard classes

Explosives Void
Flammable gases Void
Aerosols Void
Oxidising gases Void
Gases under pressure Void

· Flammable liquids Flammable liquid and vapour.

Flammable solids
 Self-reactive substances and mixtures
 Pyrophoric liquids
 Pyrophoric solids
 Self-heating substances and mixtures

Void
Void

Substances and mixtures, which emit flammable gases in contact with water
 Oxidising liquids
 Oxidising solids
 Organic peroxides
 Corrosive to metals
 Desensitised explosives

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.

8530 mg/kg (rat)

- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity

Oral

	I D/I C50	values	rolovant	for a	lassification:
•	140/14050	vaines	reievani	tor c	mssiiicanon:

LD50

123-86-4 n-butyl acetate			
Oral	LD50	10800 mg/kg (rat) (OECD 401)	
Dermal	LD50	>17600 mg/kg (rabbit)	
Inhalative	LC50/4 h	>21 mg/m3 (rat)	
108-65-6 2-methoxy-1-methylethyl acetate			

(Contd. on page 7)

Printing date 21.06.2022 Version number 9 (replaces version 8) Revision: 20.06.2022

Trade name: DUPLI-COLOR TUNING MAGIC LIGHTS Toch-up-pencil all colours

		(Contd. of page 6)	
Dermal	LD50	>5000 mg/kg (rabbit)	
Inhalative	LC50/4 h	>10000 mg/m3 (rat)	
xylene			
Oral	LD50	3523 mg/kg (rat)	
Dermal	LD50	2000 mg/kg (rabbit)	
Inhalative	LC50/4 h	29000 mg/m3 (rat)	
64-17-5 eti	64-17-5 ethanol		
Oral	LD50	10470 mg/kg (rat)	
Dermal	LD50	>2000 mg/kg (rat)	
Inhalative	LC50/4h	120 mg/l (rat)	

- · Skin corrosion/irritation No irritant effect.
- · Serious eye damage/irritation No irritating effect.
- · Respiratory or skin sensitisation No sensitising effects known.
- · STOT-single exposure May cause drowsiness or dizziness.
- · 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxi	· Aquatic toxicity:			
108-65-6 2-n	108-65-6 2-methoxy-1-methylethyl acetate			
EC50 / 48 h	>500 mg/l (daphnia magna)			
LC50 / 96 h	100-180 mg/l (oncorhynchus mykiss / Regenbogenforelle)			
xylene	xylene			
EC50 / 48 h	7.4 mg/l (daphnia magna)			
LC50 / 96 h	13.5 mg/l (fish)			
64-17-5 etha	64-17-5 ethanol			
LC50/96h	13000 mg/l (oncorhynchus mykiss / Regenbogenforelle)			
EC50 / 48 h	12900 mg/l (algae)			
LC50 / 48 h	12340 mg/l (daphnia magna)			

- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- · 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

GB

Printing date 21.06.2022 Version number 9 (replaces version 8) Revision: 20.06.2022

Trade name: DUPLI-COLOR TUNING MAGIC LIGHTS Toch-up-pencil all colours

(Contd. of page 7)

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation:

Disposal must be made according to official regulations.

Disposal must be made according to official regulations.

14.1 UN number or ID number	
ADR, IMDG, IATA	UN1263
14.2 UN proper shipping name	
ADR	1263 PAINT
IMDG, IATA	PAINT
14.3 Transport hazard class(es)	
ADR	
Class	3 (F1) Flammable liquids.
Label	3
IMDG, IATA	
Class Label	3 Flammable liquids. 3
14.4 Packing group ADR, IMDG, IATA	III
14.5 Environmental hazards:	Not applicable.
14.6 Special precautions for user	Warning: Flammable liquids.
Hazard identification number (Kemler code):	30
EMS Number:	F-E, <u>S-E</u>
Stowage Category	A
14.7 Maritime transport in bulk according to IM	
instruments	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per inner packaging. 50 ml Maximum net quantity per outer packaging: 1000 ml
Transport category	3
Tunnel restriction code	D/E

ontu. on page s

Printing date 21.06.2022 Version number 9 (replaces version 8) Revision: 20.06.2022

Trade name: DUPLI-COLOR TUNING MAGIC LIGHTS Toch-up-pencil all colours

(Contd. of page 8)

· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN ''Model Regulation'':	UN 1263 PAINT, 3, III

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50000 t
- · National regulations:

The product is subject to be labeled according with the prevailing version of the regulations on hazardous substances.

- · Other regulations, limitations and prohibitive regulations
- · Substances of very high concern (SVHC) according to REACH, Article 57

None of the ingredients is listed.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H201 Explosive; mass explosion hazard.
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H373 May cause damage to organs through prolonged or repeated exposure.

EUH066 Repeated exposure may cause skin dryness or cracking.

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

(Contd. on page 10)

Page 10/10

Safety data sheet according to 1907/2006/EC, Article 31

Version number 9 (replaces version 8) Revision: 20.06.2022 Printing date 21.06.2022

Trade name: DUPLI-COLOR TUNING MAGIC LIGHTS Toch-up-pencil all colours

(Contd. of page 9)

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic SVHC: Substances of Very High Concern vPvB: very Persistent and very Bioaccumulative

Expl. 1.1: Explosives – Division 1.1 Flam. Liq. 2: Flammable liquids – Category 2 Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 4: Acute toxicity - Category 4 Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1B: Skin sensitisation – Category 1B

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard - Category 1

* Data compared to the previous version altered.