

Page 1/9

## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 30.05.2022 Version number 14

Version number 14 (replaces version 13) Revision: 30.03.2022

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: PRESTO GASKET REMOVER 400 ML
- · Article number: 157080
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Sector of Use

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

- · Product category Other coatings and paints
- · Process category

PROC7 Industrial spraying

PROC11 Non industrial spraying

- · Application of the substance / the mixture Cleaning agent/ Cleaner
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

European Aerosols B.V.\*

Wolfraamweg 2

NL-8471 XC Wolvega

The Netherlands

Tel: +31 (0)561 694400

e-mail: sds-nl@european-aerosols.com

\*Formerly known as Motip Dupli B.V.

- · Further information obtainable from: Department Product Safety
- · 1.4 Emergency telephone number:

+31 (0)561-694400 (09:00h - 17:00h)

UK: NPIS National Poisons Information Centre Tel: +44 0344 892 0111

## SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

· Hazard pictograms



· Signal word Danger

(Contd. on page 2)

Printing date 30.05.2022 Version number 14 (replaces version 13) Revision: 30.03.2022

Trade name: PRESTO GASKET REMOVER 400 ML

(Contd. of page 1)

#### · Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

#### · Precautionary statements

- P101 If medical advice is needed, have product container or label at hand.
- P102 Keep out of reach of children.
- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- *P211* Do not spray on an open flame or other ignition source.
- *P251* Do not pierce or burn, even after use.
- P260 Do not breathe spray.
- P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
- P501 Dispose of contents / container in accordance with regional regulations.
- · Additional information:

Buildup of explosive mixtures possible without sufficient ventilation.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

## SECTION 3: Composition/information on ingredients

#### · 3.2 Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:		
CAS: 109-87-5 EINECS: 203-714-2 Reg.nr.: 01-2119664781-31	dimethoxymethane  Flam. Liq. 2, H225	25-<50%
CAS: 115-10-6 EINECS: 204-065-8 Index number: 603-019-00-8 Reg.nr.: 01-2119472128-37	dimethyl ether  Flam. Gas 1A, H220 Press. Gas (Comp.), H280	25-<50%
CAS: 646-06-0 EINECS: 211-463-5 Index number: 605-017-00-2	1,3-dioxolane Flam. Liq. 2, H225	12.5-<20%
EC number: 926-141-6 Reg.nr.: 01-2119456620-43	Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics  Asp. Tox. 1, H304 EUH066	<2.5%
CAS: 67-56-1 EINECS: 200-659-6 Index number: 603-001-00-X Reg.nr.: 01-2119433307-44	methanol  Flam. Liq. 2, H225  Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331  STOT SE 1, H370  Specific concentration limits: STOT SE 1; H370: C ≥ 10 %  STOT SE 2; H371: 3 % ≤ C < 10 %	<1%
CAS: 108-01-0 EINECS: 203-542-8 Index number: 603-047-00-0 Reg.nr.: 01-2119492298-24	2-dimethylaminoethanol  Flam. Liq. 3, H226  Acute Tox. 3, H331  Skin Corr. 1B, H314; Eye Dam. 1, H318  Acute Tox. 4, H302; Acute Tox. 4, H312; STOT SE 3, H335  Specific concentration limit: STOT SE 3; H335: C ≥ 5 %	≤0.5%

\_\_\_\_

Printing date 30.05.2022 Version number 14 (replaces version 13) Revision: 30.03.2022

Trade name: PRESTO GASKET REMOVER 400 ML

(Contd. of page 2)

· Additional information: For the wording of the listed hazard phrases refer to section 16.

### SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.
- · 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

### **SECTION 5: Firefighting measures**

- · 5.1 Extinguishing media
- · Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- 5.2 Special hazards arising from the substance or mixture

  During heating or in case of fire poisonous gases are produced.
- · 5.3 Advice for firefighters -
- · Protective equipment: Mouth respiratory protective device.

#### SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

Keep away from ignition sources.

- · 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

No special measures required.

· Information about fire - and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Keep respiratory protective device available.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurised containers.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.

(Contd. on page 4)

Printing date 30.05.2022 Version number 14 (replaces version 13) Revision: 30.03.2022

Trade name: PRESTO GASKET REMOVER 400 ML

(Contd. of page 3)

· Storage class: 2 B

· 7.3 Specific end use(s) No further relevant information available.

## SECTION 8: Exposure controls/personal protection

#### · 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

#### 109-87-5 dimethoxymethane

WEL Short-term value: 3950 mg/m³, 1250 ppm Long-term value: 3160 mg/m³, 1000 ppm

#### 115-10-6 dimethyl ether

WEL Short-term value: 958 mg/m³, 500 ppm Long-term value: 766 mg/m³, 400 ppm

#### 67-56-1 methanol

WEL Short-term value: 333 mg/m³, 250 ppm Long-term value: 266 mg/m³, 200 ppm

### 108-01-0 2-dimethylaminoethanol

WEL Short-term value: 22 mg/m³, 6 ppm Long-term value: 7.4 mg/m³, 2 ppm

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see item 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

· Respiratory protection:



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

#### Filter A2/P3

- · Hand protection Not required.
- · Material of gloves Not required.
- · Penetration time of glove material Not required.
- · Eye/face protection Not required.

### SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

Physical state
Colour:
Odour:
Odour threshold:
Melting point/freezing point:

Aerosol
Whitish
Solvent-like
Not determined.
Undetermined.

· Boiling point or initial boiling point and boiling range

range Not applicable, as aerosol.
- Flammability Not applicable.

· Lower and upper explosion limit

• *Lower*: 2.2 Vol %(109-87-5 dimethoxymethane)

(Contd. on page 5)

Printing date 30.05.2022 Version number 14 (replaces version 13) Revision: 30.03.2022

Trade name: PRESTO GASKET REMOVER 400 ML

(Contd. of page 4)

• *Upper:* 26.2 Vol % (115-10-6 dimethyl ether)

· Flash point: Not applicable, as aerosol.

• Ignition temperature: 235 °C (455 °F) (109-87-5 dimethoxymethane)

· Decomposition temperature: Not determined.

 $\cdot pH$  Mixture is non-soluble (in water).

· Viscosity:

Kinematic viscosityDynamic:Not determined.Not determined.

· Solubility

• water: Not miscible or difficult to mix.

· Partition coefficient n-octanol/water (log value) Not determined.

• Vapour pressure at 20 °C (68 °F): 4000 hPa (3000.2 mm Hg)

Density and/or relative density

Density at 20 °C (68 °F):
 Relative density
 Vapour density
 Not determined.
 Not determined.

· 9.2 Other information

· Appearance:

· Form: Aerosol

· Important information on protection of health and

environment, and on safety.

• Explosive properties: Not determined.

· Solvent content:

• Organic solvents: 84.5 %
 • VOC (EC) -- • 682.7 g/l
 • VOC-EU% 84.49 %

• VOC-EU% 84.49 % • Solids content: 0.0 %

· Change in condition

• Evaporation rate Not applicable.

· Information with regard to physical hazard classes

Explosives VoidFlammable gases Void

· Aerosols Extremely flammable aerosol. Pressurised container:

May burst if heated.

· Oxidising gases Void Void · Gases under pressure · Flammable liquids Void · Flammable solids Void · Self-reactive substances and mixtures Void · Pyrophoric liquids Void · Pyrophoric solids Void · Self-heating substances and mixtures Void

Substances and mixtures, which emit flammable gases in contact with water
Oxidising liquids
Oxidising solids
Organic peroxides
Corrosive to metals
Desensitised explosives

### SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

(Contd. on page 6)

Printing date 30.05.2022 Version number 14 (replaces version 13) Revision: 30.03.2022

Trade name: PRESTO GASKET REMOVER 400 ML

(Contd. of page 5)

- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

### SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity

LD/LC50 values relevant for classification:				
109-87-5 dimethoxymethane				
Oral	LD50	6423 mg/kg (rat)		
Dermal	LD50	>5000 mg/kg (rab) (OECD 402)		
	LC50 / 96 h	>1000 mg/l (fish) (Oncorhynchus mykiss)		
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics				
Oral	LD50	>5000 mg/kg (rat)		
Dermal	LD50	>2000 mg/kg (rat)		

- Inhalative LC50 / 4 h >5000 mg/m3 (rat) • Skin corrosion/irritation No irritant effect.
- · Serious eve damage/irritation No irritating effect.
- · Respiratory or skin sensitisation No sensitising effects known.
- · 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

### SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity:

## 109-87-5 dimethoxymethane

EC50 / 48 h | >1200 mg/l (daphnia magna) (Daphnia magna)

#### 115-10-6 dimethyl ether

EC50 / 96 h | 155 mg/l (algae)

LC50 / 48 h | >4000 mg/l (daphnia magna)

LC50/96 h > 4000 mg/l (fish)

- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- · 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

(Contd. on page 7)

Printing date 30.05.2022 Version number 14 (replaces version 13) Revision: 30.03.2022

Trade name: PRESTO GASKET REMOVER 400 ML

(Contd. of page 6)

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

## SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation:

Disposal must be made according to official regulations.

Disposal must be made according to official regulations.

UN1950
0111730
1950 AEROSOLS
AEROSOLS
AEROSOLS, flammable
2 5F Gases.
2.1
2.1 Gases.
2.1
not regulated
Not applicable.
Warning: Gases.
-
F-D,S-U
SWI Protected from sources of heat.
SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity
above 1 litre: Category B. For WASTE AEROSOLS:
Category C, Clear of living quarters.
SG69 For AEROSOLS with a maximum capacity of 1
litre:
Segregation as for class 9. Stow "separated from" class 1 except for division 1.4.

(Contd. on page 8)

Printing date 30.05.2022 Version number 14 (replaces version 13) Revision: 30.03.2022

Trade name: PRESTO GASKET REMOVER 400 ML

	(Contd. of page
	For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS:
	Segregation as for the appropriate subdivision of class  2.
· 14.7 Maritime transport in bulk accord	ling to IMO
instruments	Not applicable.
· Transport/Additional information:	
· <i>ADR</i>	
· Limited quantities (LQ)	IL
$\cdot$ Excepted quantities $(\widetilde{EQ})$	Code: E0
· · · · · · · · · · · · · · · · ·	Not permitted as Excepted Quantity
· Transport category	2
Tunnel restriction code	D
· IMDG	
· Limited quantities (LQ)	IL
Excepted quantities (EQ)	Code: E0
	Not permitted as Excepted Quantity
	Code: E0
	Not permitted as Excepted Quantity
· UN "Model Regulation":	UN 1950 AEROSOLS, 2.1

### SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P3a FLAMMABLE AEROSOLS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- $\cdot \textit{Qualifying quantity (tonnes) for the application of upper-tier requirements } 500~t$
- · National regulations:
- · Other regulations, limitations and prohibitive regulations
- · Substances of very high concern (SVHC) according to REACH, Article 57

None of the ingredients is listed.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H301 Toxic if swallowed.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H311 Toxic in contact with skin.

(Contd. on page 9)

Version number 14 (replaces version 13) Revision: 30.03.2022 Printing date 30.05.2022

Trade name: PRESTO GASKET REMOVER 400 ML

(Contd. of page 8) H312 Harmful in contact with skin. H314 Causes severe skin burns and eye damage. H318 Causes serious eye damage. H331 Toxic if inhaled. H335 May cause respiratory irritation. H370 Causes damage to organs. EUH066 Repeated exposure may cause skin dryness or cracking. · Department issuing SDS: R&D legislation and regulatory advisor · Contact: e-mail: sds-nl@european-aerosols.com · Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic SVHC: Substances of Very High Concern vPvB: very Persistent and very Bioaccumulative Flam. Gas 1A: Flammable gases - Category 1A Aerosol 1: Aerosols - Category 1 Press. Gas (Comp.): Gases under pressure - Compressed gas Flam. Liq. 2: Flammable liquids - Category 2 Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 3: Acute toxicity - Category 3 Acute Tox. 4: Acute toxicity - Category 4 Skin Corr. 1B: Skin corrosion/irritation - Category 1B Eye Dam. 1: Serious eye damage/eye irritation - Category 1

STOT SE 1: Specific target organ toxicity (single exposure) – Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Asp. Tox. 1: Aspiration hazard - Category 1

\* Data compared to the previous version altered.