

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.07.2022

Version number 6 (replaces version 5)

Revision: 01.07.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: **Colorworks Metallic**

Article number:

918580 - 585, 938580 - 585, 395758alt, 395765alt, 395772alt, 395789alt, 395796alt, 395802alt, 928580alt - 585alt

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Sector of Use

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

SU21 Consumer uses: Private households / general public / consumers

Product category PC9a Coatings and paints, thinners, paint removers

Process category

PROC7 Industrial spraying

PROC11 Non industrial spraying

Application of the substance / the mixture Lacquer

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

European Aerosols GmbH*

Kurt Vogelsang Strasse 6

D-74855 Haßmersheim

Tel.: +49 (0) 6266 750

e-mail: sds-de@european-aerosols.com

*Formerly known as Motip Dupli GmbH

Further information obtainable from: Department Product Safety

1.4 Emergency telephone number:

Tel.: +49 6266-75-310

Fax +49 6266-75-362

(Mo - Th 08:00 am - 04:00 pm, Fr 08:00 am - 00:30 pm)

UK:

Public emergency phone no: 111

Only for healthcare professionals: 0344 892 0111

Ireland:

Poison center if child has been poisoned: 01 809 2166 (8:00 am - 10:00 pm, 7 days)

Only for healthcare professionals: 01 809 2566 (24 h / 7 days)

Tox Info Suisse 145 (24-h-emergency number)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



flame

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.07.2022

Version number 6 (replaces version 5)

Revision: 01.07.2022

Trade name: Colorworks Metallic

(Contd. of page 1)



Eye Irrit. 2 H319

Causes serious eye irritation.

STOT SE 3 H336

May cause drowsiness or dizziness.

· 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

· Hazard pictograms



GHS02



GHS07

· Signal word Danger

· Hazard-determining components of labelling:

acetone

n-butyl acetate

2-methoxy-1-methylethyl acetate

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P260 Do not breathe spray.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents / container in accordance with regional regulations.

· Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

Buildup of explosive mixtures possible without sufficient ventilation.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· PBT: Not applicable.

· vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:

| | | |
|--|--|-----------|
| CAS: 67-64-1 EINECS: 200-662-2 Index number: 606-001-00-8 Reg.nr.: 01-2119471330-49 | acetone Flam. Liq. 2, H225 Eye Irrit. 2, H319; STOT SE 3, H336 EUH066 | 25-<50% |
| CAS: 74-98-6 EINECS: 200-827-9 Index number: 601-003-00-5 Reg.nr.: 01-2119486944-21 | propane Flam. Gas 1A, H220 Press. Gas (Comp.), H280 | 12.5-<20% |

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.07.2022

Version number 6 (replaces version 5)

Revision: 01.07.2022

Trade name: Colorworks Metallic

(Contd. of page 2)

| | | |
|---|---|-----------|
| CAS: 123-86-4 EINECS: 204-658-1 Index number: 607-025-00-1 Reg.nr.: 01-2119485493-29 | <i>n</i> -butyl acetate ⚠ Flam. Liq. 3, H226 ⚠ STOT SE 3, H336 EUH066 | 10-<12.5% |
| CAS: 106-97-8 EINECS: 203-448-7 Index number: 601-004-00-0 Reg.nr.: 01-2119474691-32 | butane (containing < 0,1 % butadiene (203-450-8)) ⚠ Flam. Gas 1A, H220 Press. Gas (Comp.), H280 | 10-<12.5% |
| CAS: 108-65-6 EINECS: 203-603-9 Index number: 607-195-00-7 Reg.nr.: 01-2119475791-29 | 2-methoxy-1-methylethyl acetate ⚠ Flam. Liq. 3, H226 ⚠ STOT SE 3, H336 | 5-<10% |
| CAS: 75-28-5 EINECS: 200-857-2 Index number: 601-004-00-0 Reg.nr.: 01-2119485395-27 | isobutane (containing < 0,1 % butadiene (203-450-8)) ⚠ Flam. Gas 1A, H220 Press. Gas (Comp.), H280 | 2.5-<5% |
| CAS: 9004-70-0 | cellulose nitrate ⚠ Expl. 1.1, H201 | 2.5-<5% |
| EC number: 905-588-0 Index number: 601-022-00-9 Reg.nr.: 01-2119488216-32 | xylene ⚠ Flam. Liq. 3, H226 ⚠ STOT RE 2, H373; Asp. Tox. 1, H304 ⚠ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335 | <2.5% |
| CAS: 64-17-5 EINECS: 200-578-6 Index number: 603-002-00-5 Reg.nr.: 01-2119457610-43 | ethanol ⚠ Flam. Liq. 2, H225 ⚠ Eye Irrit. 2, H319 Specific concentration limit: Eye Irrit. 2; H319: C ≥ 50 % | <2.5% |

Additional information:

The content of Benzene (EINECS-Nr. 200-753-7) in the ingredients is less than 0,1% (Note P Annex 1A 1272/2008 EU), so the classification as carcinogen need not to apply.

xylene: Contains ethylbenzene CAS 100-41-4

CAS 9004-70-0: GB CLP Note T

For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

• **After inhalation:** Supply fresh air; consult doctor in case of complaints.

• **After skin contact:** Generally the product does not irritate the skin.

• **After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

• **After swallowing:** Drink plenty of water and provide fresh air. Call for a doctor immediately.

• **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.

• **4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

• **Suitable extinguishing agents:**

CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

Use fire extinguishing methods suitable to surrounding conditions.

5.2 Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

5.3 Advice for firefighters -

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.07.2022

Version number 6 (replaces version 5)

Revision: 01.07.2022

Trade name: Colorworks Metallic

(Contd. of page 3)

· **Protective equipment:** Mouth respiratory protective device.

SECTION 6: Accidental release measures

· **6.1 Personal precautions, protective equipment and emergency procedures**

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

Keep away from ignition sources.

· **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.

· **6.3 Methods and material for containment and cleaning up:**

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· **6.4 Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· **7.1 Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace.

· **Information about fire - and explosion protection:**

Keep ignition sources away - Do not smoke.

Keep respiratory protective device available.

· **7.2 Conditions for safe storage, including any incompatibilities**

· **Storage:**

· **Requirements to be met by storerooms and receptacles:**

Observe official regulations on storing packagings with pressurised containers.

· **Information about storage in one common storage facility:** Not required.

· **Further information about storage conditions:** Keep container tightly sealed.

· **Storage class:** 2 B

· **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

· **8.1 Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**

67-64-1 acetone

WEL Short-term value: 3620 mg/m³, 1500 ppm

Long-term value: 1210 mg/m³, 500 ppm

123-86-4 n-butyl acetate

WEL Short-term value: 966 mg/m³, 200 ppm

Long-term value: 724 mg/m³, 150 ppm

106-97-8 butane (containing < 0,1 % butadiene (203-450-8))

WEL Short-term value: 1810 mg/m³, 750 ppm

Long-term value: 1450 mg/m³, 600 ppm

Carc (if more than 0.1% of buta-1.3-diene)

108-65-6 2-methoxy-1-methylethyl acetate

WEL Short-term value: 548 mg/m³, 100 ppm

Long-term value: 274 mg/m³, 50 ppm

Sk

xylene

WEL Short-term value: 441 mg/m³, 100 ppm

Long-term value: 220 mg/m³, 50 ppm

Sk; BMGV

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.07.2022

Version number 6 (replaces version 5)

Revision: 01.07.2022

Trade name: Colorworks Metallic

(Contd. of page 4)

64-17-5 ethanolWEL Long-term value: 1920 mg/m³, 1000 ppm**· Ingredients with biological limit values:****xylene**

BMGV 650 mmol/mol creatinine
 Medium: urine
 Sampling time: post shift
 Parameter: methyl hippuric acid

· Additional information: The lists valid during the making were used as basis.**· 8.2 Exposure controls****· Appropriate engineering controls** No further data; see item 7.**· Individual protection measures, such as personal protective equipment****· General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

Avoid contact with the eyes.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Filter A2/P3

· Hand protection

Protective gloves

· Material of gloves

Butyl rubber, BR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· Penetration time of glove material

Butyl rubber gloves with a thickness of 0.4 mm are resistant to:

Acetone: 480 min

Butyl acetate: 60 min

Ethyl acetate: 170 min

Xylene: 42 min

Butyl rubber gloves with a thickness of 0.4 mm are solvent resistant for 42- 480 minutes. As protective measure, we recommend that users and responsible persons for work safety assume solvent resistance length of 42 minutes. Considering the data in section 3 of this SDS, one can assume longer resistance length in particular cases.

· Eye/face protection

Tightly sealed goggles

GB

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.07.2022

Version number 6 (replaces version 5)

Revision: 01.07.2022

Trade name: Colorworks Metallic

(Contd. of page 5)

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

| | |
|--|--|
| · Physical state | Aerosol |
| · Colour: | According to product specification |
| · Odour: | Characteristic |
| · Odour threshold: | Not determined. |
| · Melting point/freezing point: | Undetermined. |
| · Boiling point or initial boiling point and boiling range | Not applicable, as aerosol. |
| · Flammability | Not applicable. |
| · Lower and upper explosion limit | |
| · Lower: | 1.2 Vol % (123-86-4 n-butyl acetate) |
| · Upper: | 13 Vol % (67-64-1 acetone) |
| · Flash point: | Not applicable, as aerosol. |
| · Ignition temperature: | 333 °C (631.4 °F) (108-65-6 2-methoxy-1-methylethyl acetate) |
| · Decomposition temperature: | Not determined. |
| · pH | Mixture is non-soluble (in water). |
| · Viscosity: | |
| · Kinematic viscosity | Not determined. |
| · Dynamic: | Not determined. |
| · Solubility | |
| · water: | Not miscible or difficult to mix. |
| · Partition coefficient n-octanol/water (log value) | Not determined. |
| · Vapour pressure at 20 °C (68 °F): | 8300 hPa (6225.5 mm Hg) (74-98-6 propane) |
| · Density and/or relative density | |
| · Density at 20 °C (68 °F): | 0.8 g/cm ³ (6.7 lbs/gal) |
| · Relative density | Not determined. |
| · Vapour density | Not determined. |

· 9.2 Other information

| | |
|---|-----------------|
| · Appearance: | |
| · Form: | Aerosol |
| · Important information on protection of health and environment, and on safety. | |
| · Explosive properties: | Not determined. |
| · Solvent content: | |
| · Organic solvents: | 90.4 % |
| · VOC (EC) | --- |
| | 723.3 g/l |
| · VOC-EU% | 90.41 % |
| · Solids content: | 8.8 % |
| · Change in condition | |
| · Evaporation rate | Not applicable. |

· Information with regard to physical hazard classes

| | |
|---|--|
| · Explosives | Void |
| · Flammable gases | Void |
| · Aerosols | Extremely flammable aerosol. Pressurised container: May burst if heated. |
| · Oxidising gases | Void |
| · Gases under pressure | Void |
| · Flammable liquids | Void |
| · Flammable solids | Void |
| · Self-reactive substances and mixtures | Void |
| · Pyrophoric liquids | Void |
| · Pyrophoric solids | Void |

(Contd. on page 7)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 01.07.2022

Version number 6 (replaces version 5)

Revision: 01.07.2022

Trade name: Colorworks Metallic

(Contd. of page 6)

- | | |
|--|------|
| · Self-heating substances and mixtures | Void |
| · Substances and mixtures, which emit flammable gases in contact with water | Void |
| · Oxidising liquids | Void |
| · Oxidising solids | Void |
| · Organic peroxides | Void |
| · Corrosive to metals | Void |
| · Desensitised explosives | Void |

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity**

· **LD/LC50 values relevant for classification:**

67-64-1 acetone

| | | |
|------------|-----------|-----------------------|
| Oral | LD50 | 5800 mg/kg (rat) |
| Dermal | LD50 | >15800 mg/kg (rabbit) |
| Inhalative | LC50 / 4h | 76 mg/l (rat) |

123-86-4 n-butyl acetate

| | | |
|------------|------------|------------------------------|
| Oral | LD50 | 10800 mg/kg (rat) (OECD 401) |
| Dermal | LD50 | >17600 mg/kg (rabbit) |
| Inhalative | LC50 / 4 h | >21 mg/m ³ (rat) |

108-65-6 2-methoxy-1-methylethyl acetate

| | | |
|------------|------------|--------------------------------|
| Oral | LD50 | 8530 mg/kg (rat) |
| Dermal | LD50 | >5000 mg/kg (rabbit) |
| Inhalative | LC50 / 4 h | >10000 mg/m ³ (rat) |

xylene

| | | |
|------------|------------|-------------------------------|
| Oral | LD50 | 3523 mg/kg (rat) |
| Dermal | LD50 | 2000 mg/kg (rabbit) |
| Inhalative | LC50 / 4 h | 29000 mg/m ³ (rat) |

64-17-5 ethanol

| | | |
|------------|-----------|-------------------|
| Oral | LD50 | 10470 mg/kg (rat) |
| Dermal | LD50 | >2000 mg/kg (rat) |
| Inhalative | LC50 / 4h | 120 mg/l (rat) |

- **Skin corrosion/irritation** No irritant effect.
- **Serious eye damage/irritation** Causes serious eye irritation.
- **Respiratory or skin sensitisation** No sensitising effects known.
- **STOT-single exposure** May cause drowsiness or dizziness.

(Contd. on page 8)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 01.07.2022

Version number 6 (replaces version 5)

Revision: 01.07.2022

Trade name: Colorworks Metallic

(Contd. of page 7)

· **11.2 Information on other hazards**· **Endocrine disrupting properties**

None of the ingredients is listed.

* **SECTION 12: Ecological information**· **12.1 Toxicity**· **Aquatic toxicity:****67-64-1 acetone**

| | |
|-------------|-------------------------------------|
| LC50/96h | 8300 mg/l (fish) |
| EC50/96h | 7200 mg/l (algae) |
| LC50 / 48 h | 8450 mg/l (crustacean (water flea)) |

108-65-6 2-methoxy-1-methylethyl acetate

| | |
|-------------|--|
| EC50 / 48 h | >500 mg/l (daphnia magna) |
| LC50 / 96 h | 100-180 mg/l (oncorhynchus mykiss / Regenbogenforelle) |

xylene

| | |
|-------------|--------------------------|
| EC50 / 48 h | 7.4 mg/l (daphnia magna) |
| LC50 / 96 h | 13.5 mg/l (fish) |

64-17-5 ethanol

| | |
|-------------|--|
| LC50/96h | 13000 mg/l (oncorhynchus mykiss / Regenbogenforelle) |
| EC50 / 48 h | 12900 mg/l (algae) |
| LC50 / 48 h | 12340 mg/l (daphnia magna) |

· **12.2 Persistence and degradability** No further relevant information available.· **12.3 Bioaccumulative potential** No further relevant information available.· **12.4 Mobility in soil** No further relevant information available.· **12.5 Results of PBT and vPvB assessment**· **PBT:** Not applicable.· **vPvB:** Not applicable.· **12.6 Endocrine disrupting properties**

The product does not contain substances with endocrine disrupting properties.

· **12.7 Other adverse effects**· **Additional ecological information:**· **General notes:**

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

* **SECTION 13: Disposal considerations**· **13.1 Waste treatment methods**· **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· **Uncleaned packaging:**· **Recommendation:**

Disposal must be made according to official regulations.

Disposal must be made according to official regulations.

GB

(Contd. on page 9)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 01.07.2022

Version number 6 (replaces version 5)

Revision: 01.07.2022

Trade name: Colorworks Metallic

(Contd. of page 8)

SECTION 14: Transport information

- 14.1 UN number or ID number
- ADR, IMDG, IATA

UN1950

- 14.2 UN proper shipping name
- ADR
- IMDG
- IATA

1950 AEROSOLS
AEROSOLS
AEROSOLS, flammable

- 14.3 Transport hazard class(es)
- ADR



- Class
- Label

2 5F Gases.
2.1

- IMDG, IATA



- Class
- Label

2.1 Gases.
2.1

- 14.4 Packing group
- ADR, IMDG, IATA

not regulated

- 14.5 Environmental hazards:

Not applicable.

- 14.6 Special precautions for user
- Hazard identification number (Kemler code):
- EMS Number:
- Stowage Code

Warning: Gases.
-
F-D,S-U
SW1 Protected from sources of heat.
SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.
SG69 For AEROSOLS with a maximum capacity of 1 litre:
Segregation as for class 9. Stow "separated from" class 1 except for division 1.4.
For AEROSOLS with a capacity above 1 litre:
Segregation as for the appropriate subdivision of class 2.
For WASTE AEROSOLS:
Segregation as for the appropriate subdivision of class 2.

- Segregation Code

- 14.7 Maritime transport in bulk according to IMO instruments

Not applicable.

- Transport/Additional information:

- ADR
- Limited quantities (LQ)
- Excepted quantities (EQ)

1L
Code: E0
Not permitted as Excepted Quantity

- Transport category
- Tunnel restriction code

2
D

(Contd. on page 10)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 01.07.2022

Version number 6 (replaces version 5)

Revision: 01.07.2022

Trade name: Colorworks Metallic

(Contd. of page 9)

| | |
|-----------------------------------|--|
| · IMDG | |
| · Limited quantities (LQ) | 1L |
| · Excepted quantities (EQ) | Code: E0 Not permitted as Excepted Quantity |
| · UN "Model Regulation": | UN 1950 AEROSOLS, 2.1 |

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category P3a** FLAMMABLE AEROSOLS
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 150 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t
- **LIST OF SUBSTANCES SUBJECT TO AUTHORISATION (UK ANNEX XIV)**

- **Regulation (EC) No 273/2004 on drug precursors**

67-64-1 acetone

3

- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

- H201 Explosive; mass explosion hazard.
- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H373 May cause damage to organs through prolonged or repeated exposure.
- EUH066 Repeated exposure may cause skin dryness or cracking.

· **Abbreviations and acronyms:**

- RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
- IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)
- ICAO: International Civil Aviation Organisation
- ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- VOC: Volatile Organic Compounds (USA, EU)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative
- Expl. 1.1: Explosives – Division 1.1
- Flam. Gas 1A: Flammable gases – Category 1A

(Contd. on page 11)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 01.07.2022

Version number 6 (replaces version 5)

Revision: 01.07.2022

Trade name: Colorworks Metallic

(Contd. of page 10)

Aerosol 1: Aerosols – Category 1
Press. Gas (Comp.): Gases under pressure – Compressed gas
Flam. Liq. 2: Flammable liquids – Category 2
Flam. Liq. 3: Flammable liquids – Category 3
Acute Tox. 4: Acute toxicity – Category 4
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
Asp. Tox. 1: Aspiration hazard – Category 1

· *** Data compared to the previous version altered.**

GB