

Page 1/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 10.12.2021 Version number 9 (replaces version 8) Revision: 10.12.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: Motip Touch up pencil Kompakt
- · Article number:

M900101 - M900107, M907001 - M907238, M941000 - M946870, M950980, M951000 - M956999, M30000alt, 302480alt - 302497alt, 163791

• 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.

· Sector of Use

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen) SU21 Consumer uses: Private households / general public / consumers

- · Product category PC9a Coatings and paints, thinners, paint removers
- · Process category PROC10 Roller application or brushing
- · Application of the substance / the mixture Lacquer
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier: European Aerosols GmbH* Kurt Vogelsang Strasse 6 D-74855 Haßmersheim

Tel.: +49 (0) 6266 750

e-mail: sds-de@european-aerosols.com

- *Formerly known as Motip Dupli GmbH
- · Further information obtainable from: Department Product Safety
- · 1.4 Emergency telephone number:

Tel.:+49 6266-75-310 *Fax* +49 6266-75-362

(Mo - Th 08:00 am - 04:00 pm, Fr 08:00 am - 00:30 pm)

UK:

Public emergeny phone no: 111

Only for healthcare professionals: 0344 892 0111

Ireland

Poison center if childs have been poisened: 01 809 2166 (8:00 am - 10:00 pm, 7 days)

Only for healthcare professionals: 01 809 2566 (24 h / 7 days)

Tox Info Suisse 145 (24-h-emergency number)

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



Flam. Liq. 3 H226 Flammable liquid and vapour.



(Contd. on page 2)

Version number 9 (replaces version 8) Printing date 10.12.2021 Revision: 10.12.2021

Trade name: Motip Touch up pencil - Kompakt

(Contd. of page 1)

STOT SE 3 H336 May cause drowsiness or dizziness.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms





GHS02

GHS07

- · Signal word Warning
- · Hazard-determining components of labelling:

n-butyl acetate

2-methoxy-1-methylethyl acetate

· Hazard statements

H226 Flammable liquid and vapour.

H336 May cause drowsiness or dizziness.

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P260 Do not breathe vapours.

P271 Use only outdoors or in a well-ventilated area.

P312 Call a POISON CENTER/doctor if you feel unwell.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents / container in accordance with regional regulations.

· Additional information:

In container sizes up to 125ml the labelling can be reduced in accordance with Article 29 (2) in connection with Annex I No. 1.5.2.

EUH066 Repeated exposure may cause skin dryness or cracking.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 123-86-4	n-butyl acetate	25-<50%
EINECS: 204-658-1	© Flam. Liq. 3, H226	
Index number: 607-025-00-1	♦ STOT SĒ 3, H336	
Reg.nr.: 01-2119485493-29	EUH066	10 12 70/
CAS: 9004-70-0	cellulose nitrate	10-<12.5%
	♦ Flam. Sol. 1, H228	
EC number: 905-588-0	xylene	5-<10%
Index number: 601-022-00-9	🕸 Flam. Liq. 3, H226	
Reg.nr.: 01-2119488216-32	♦ STOT RĒ 2, H373; Asp. Tox. 1, H304	
	Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2,	
	H315; Eye Irrit. 2, H319; STOT SE 3, H335	
CAS: 108-65-6	2-methoxy-1-methylethyl acetate	2.5-<5%
EINECS: 203-603-9	⋄ Flam. Liq. 3, H226	
Index number: 607-195-00-7	♦ STOT SE 3, H336	
Reg.nr.: 01-2119475791-29		

(Contd. on page 3)

Printing date 10.12.2021 Version number 9 (replaces version 8) Revision: 10.12.2021

Trade name: Motip Touch up pencil - Kompakt

	(Contd. of page 2)
CAS: 64-17-5 EINECS: 200-578-6 Index number: 603-002-00-5 Reg.nr.: 01-2119457610-43	ethanol → Flam. Liq. 2, H225 → Eye Irrit. 2, H319 Specific concentration limit: Eye Irrit. 2; H319: C ≥ 50 %	2.5-<5%
CAS: 13463-67-7 EINECS: 236-675-5 Index number: 022-006-00-2 Reg.nr.: 01-2119489379-17	titanium dioxide © Carc. 2, H351	2.5-<5%
CAS: 7429-90-5 EINECS: 231-072-3 Index number: 013-002-00-1 Reg.nr.: 01-2119529243-45-xxxx	aluminium powder (stabilised) Flam. Sol. 2, H228	<2.5%

· Additional information:

The content of Benzene (EINECS-Nr. 200-753-7) in the ingredients is less than 0,1% (Note P Annex 1A 1272/2008 EU), so the classification as carcinogen need not to apply.

xylene: Contains ethylbenzene CAS 100-41-4

For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

- · 5.3 Advice for firefighters -
- · Protective equipment: Mouth respiratory protective device.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

Keep away from ignition sources.

- $\cdot \textbf{ 6.2 Environmental precautions:} \ \textit{Do not allow to enter sewers/ surface or ground water.}$
- · 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

(Contd. on page 4)

Version number 9 (replaces version 8) Printing date 10.12.2021 Revision: 10.12.2021

Trade name: Motip Touch up pencil - Kompakt

See Section 13 for disposal information.

(Contd. of page 3)

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Use only in well ventilated areas.

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

- · 7.2 Conditions for safe storage, including any incompatibilities
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 3
- \cdot 7.3 *Specific end use*(s) *No further relevant information available.*

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

Ingradiants	with limit value	that require	monitorina a	t the workplace:
· Ingreatents	with time value:	s mai reamre	monuorny a	t the workbluce:

123-86-4 n-butyl acetate

WEL Short-term value: 966 mg/m³, 200 ppm Long-term value: 724 mg/m³, 150 ppm

xylene

WEL Short-term value: 441 mg/m³, 100 ppm Long-term value: 220 mg/m³, 50 ppm

Sk; BMGV

108-65-6 2-methoxy-1-methylethyl acetate

WEL Short-term value: 548 mg/m³, 100 ppm Long-term value: 274 mg/m³, 50 ppm

64-17-5 ethanol

WEL Long-term value: 1920 mg/m³, 1000 ppm

· Ingredients with biological limit values:

xylene

BMGV 650 mmol/mol creatinine

Medium: urine

Sampling time: post shift Parameter: methyl hippuric acid

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see item 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

(Contd. on page 5)

Printing date 10.12.2021 Version number 9 (replaces version 8) Revision: 10.12.2021

Trade name: Motip Touch up pencil - Kompakt

· Respiratory protection:

(Contd. of page 4)



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Filter A2/P3

- · Hand protection Not required.
- · Material of gloves Not required.
- · Penetration time of glove material Not required.
- · Eye/face protection



Tightly sealed goggles

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Physical state Fluid

· Colour: According to product specification

Odour: Characteristic
 Odour threshold: Not determined.
 Melting point/freezing point: Undetermined.

· Boiling point or initial boiling point and boiling

range 78 °C (172.4 °F)
• Flammability Not applicable.

· Lower and upper explosion limit

• Lower: 1.2 Vol % (123-86-4 n-butyl acetate)
 • Upper: 15 Vol % (9004-70-0 cellulose nitrate)

• Flash point: 27 °C (80.6 °F) • Decomposition temperature: Not determined.

 $\cdot pH$ Mixture is non-soluble (in water).

· Viscosity:

• Kinematic viscosity at 20 °C (68 °F) 60 s (ISO 4 mm) • Dynamic: Not determined.

· Solubility

• water: Not miscible or difficult to mix.

· Partition coefficient n-octanol/water (log value) Not determined.

• Vapour pressure at 20 °C (68 °F): 13 hPa (9.8 mm Hg) (123-86-4 n-butyl acetate)

· Density and/or relative density

Density at 20 °C (68 °F):
 Relative density
 Vapour density
 I g/cm³ (8.3 lbs/gal)
 Not determined.
 Not determined.

· 9.2 Other information

· Appearance:

· Form: Fluid

· Important information on protection of health and

environment, and on safety.

• Ignition temperature: $180 \, ^{\circ}\text{C} \, (356 \, ^{\circ}\text{F})$

• Explosive properties: Product is not explosive. However, formation of

explosive air/vapour mixtures are possible.

· Solvent content:

· Organic solvents: 62.7 %

(Contd. on page 6)

Printing date 10.12.2021 Version number 9 (replaces version 8) Revision: 10.12.2021

Trade name: Motip Touch up pencil - Kompakt

		(Contd. of page
VOC (EC)		
	626.6 g/l	
VOC-EU%	62.66 %	
Solids content:	35.0 %	
Change in condition		
Evaporation rate	Not determined.	
Information with regard to physical hazard o	classes	
Explosives	Void	
Flammable gases	Void	
Aerosols	Void	
Oxidising gases	Void	
Gases under pressure	Void	
Flammable liquids	Flammable liquid and vapour.	
Flammable solids	Void	
Self-reactive substances and mixtures	Void	
Pyrophoric liquids	Void	
Pyrophoric solids	Void	
Self-heating substances and mixtures	Void	
Substances and mixtures, which emit flamm	able	
gases in contact with water	Void	
Oxidising liquids	Void	
Oxidising solids	Void	
Organic peroxides	Void	
Corrosive to metals	Void	
Desensitised explosives	Void	

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity

· LD/LC50 values relevant for classification:		
123-86-4 n	ı-butyl aceto	nte
Oral	LD50	10800 mg/kg (rat) (OECD 401)
Dermal	LD50	>17600 mg/kg (rabbit)
Inhalative	LC50/4 h	>21 mg/m3 (rat)
xylene		
Oral	LD50	3523 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rabbit)
Inhalative	LC50/4 h	29000 mg/m3 (rat)
108-65-6 2	-methoxy-1	-methylethyl acetate
Oral	LD50	8530 mg/kg (rat)
Dermal	LD50	>5000 mg/kg (rabbit)
		(Contd. on page 7)

Contd. on page

Printing date 10.12.2021 Version number 9 (replaces version 8) Revision: 10.12.2021

Trade name: Motip Touch up pencil - Kompakt

			(Contd. of page 6)
	Inhalative	LC50/4 h	>10000 mg/m3 (rat)
Ī	64-17-5 eti	hanol	
ı	Oral	LD50	10470 mg/kg (rat)
	Dermal	LD50	>2000 mg/kg (rat)
	Inhalative	LC50/4h	120 mg/l (rat)

- · Skin corrosion/irritation No irritant effect.
- · Serious eye damage/irritation No irritating effect.
- · Respiratory or skin sensitisation No sensitising effects known.
- · STOT-single exposure May cause drowsiness or dizziness.
- · 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxic	· Aquatic toxicity:		
xylene			
EC50 / 48 h	7.4 mg/l (daphnia magna)		
LC50 / 96 h	13.5 mg/l (fish)		
108-65-6 2-n	nethoxy-1-methylethyl acetate		
EC50 / 48 h	>500 mg/l (daphnia magna)		
LC50 / 96 h	100-180 mg/l (oncorhynchus mykiss / Regenbogenforelle)		
64-17-5 etha	nol		
LC50/96h	13000 mg/l (oncorhynchus mykiss / Regenbogenforelle)		
EC50 / 48 h	12900 mg/l (algae)		
LC50 / 48 h	12340 mg/l (daphnia magna)		

- · 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- · 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation:

Disposal must be made according to official regulations.

(Contd. on page 8)

Printing date 10.12.2021 Version number 9 (replaces version 8) Revision: 10.12.2021

Trade name: Motip Touch up pencil - Kompakt

Disposal must be made according to official regulations.

(Contd. of page 7)

SECTION 14: Transport information	
14.1 UN number or ID number ADR, IMDG, IATA	UN1263
14.2 UN proper shipping name	
ADR	1263 PAINT
IMDG, IATA	PAINT
14.3 Transport hazard class(es)	
ADR	
Class	3 (F1) Flammable liquids.
Label	3
IMDG, IATA	
Class	3 Flammable liquids.
Label	3
14.4 Packing group ADR, IMDG, IATA	III
14.5 Environmental hazards:	Not applicable.
14.6 Special precautions for user	Warning: Flammable liquids.
Hazard identification number (Kemler code):	30
EMS Number:	<i>F-E,<u>S-E</u></i>
Stowage Category	A
14.7 Maritime transport in bulk according to IM	10
instruments	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
_	Maximum net quantity per outer packaging: 1000 ml
Transport category	3 D.//
Tunnel restriction code	D/E
IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
UN "Model Regulation":	UN 1263 PAINT, 3, III

Printing date 10.12.2021 Version number 9 (replaces version 8) Revision: 10.12.2021

Trade name: Motip Touch up pencil - Kompakt

(Contd. of page 8)

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50000 t
- · National regulations:

The product is subject to be labeled according with the prevailing version of the regulations on hazardous substances.

- · Other regulations, limitations and prohibitive regulations
- · Substances of very high concern (SVHC) according to REACH, Article 57

None of the ingredients is listed.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H228 Flammable solid.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H351 Suspected of causing cancer.
- H373 May cause damage to organs through prolonged or repeated exposure.

EUH066 Repeated exposure may cause skin dryness or cracking.

· Abbreviations and acronyms:

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

SVHC: Substances of Very High Concern

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids - Category 3

Flam. Sol. 1: Flammable solids - Category 1

Flam. Sol. 2: Flammable solids – Category 2

Acute Tox. 4: Acute toxicity - Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

(Contd. on page 10)

Page 10/10

Safety data sheet according to 1907/2006/EC, Article 31

Version number 9 (replaces version 8) Printing date 10.12.2021 Revision: 10.12.2021

Trade name: Motip Touch up pencil - Kompakt

Carc. 2: Carcinogenicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2 Asp. Tox. 1: Aspiration hazard – Category 1

 \cdot * Data compared to the previous version altered.

(Contd. of page 9)