

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 15.05.2023

Version number 3 (replaces version 2)

Revision: 30.03.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

· **Trade name:** NICRO 203 MOULD RELEASE AGENT 400 ML (Aerosol)

· **Article number:** 302237

· **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.

· **Sector of Use**

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

· **Product category** Other coatings and paints

· **Process category**

PROC7 Industrial spraying

PROC11 Non industrial spraying

· **Application of the substance / the mixture** Demulsifier

1.3 Details of the supplier of the safety data sheet

· **Manufacturer/Supplier:**

European Aerosols B.V.*

Wolfraamweg 2

NL-8471 XC Wolvega

The Netherlands

Tel : +31 (0)561 694400

e-mail: sds-nl@european-aerosols.com

*Formerly known as Motip Dupli B.V.

· **Further information obtainable from:** Department Product Safety

· **1.4 Emergency telephone number:**

+31 (0)561-694400 (09:00h - 17:00h)

UK: NPIS National Poisons Information Centre Tel: +44 0344 892 0111

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

· **Classification according to Regulation (EC) No 1272/2008**



flame

Aerosol 1

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



Skin Irrit. 2

H315

Causes skin irritation.

Aquatic Chronic 3 H412

Harmful to aquatic life with long lasting effects.

2.2 Label elements

· **Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the GB CLP regulation.

(Contd. on page 2)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 15.05.2023

Version number 3 (replaces version 2)

Revision: 30.03.2022

Trade name: NICRO 203 MOULD RELEASE AGENT 400 ML (Aerosol)

(Contd. of page 1)

· Hazard pictograms


GHS02 GHS07

· Signal word *Danger*
· Hazard statements
H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.
H315 Causes skin irritation.
H412 Harmful to aquatic life with long lasting effects.
· Precautionary statements
P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P260 Do not breathe spray.
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501 Dispose of contents / container in accordance with regional regulations.
· Additional information:
Buildup of explosive mixtures possible without sufficient ventilation.
· 2.3 Other hazards
· Results of PBT and vPvB assessment
· PBT: Not applicable.

· vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures
· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:

CAS: 109-87-5 EINECS: 203-714-2 Reg.nr.: 01-2119664781-31	dimethoxymethane ⚠ Flam. Liq. 2, H225	50-<75%
EC number: 921-024-6 Reg.nr.: 01-2119475514-35	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane ⚠ Flam. Liq. 2, H225 ⚠ Asp. Tox. 1, H304 ⚠ Aquatic Chronic 2, H411 ⚠ Skin Irrit. 2, H315; STOT SE 3, H336	12.5-<20%
CAS: 124-38-9 EINECS: 204-696-9	carbon dioxide ⚠ Press. Gas (Liq.), H280	5-<10%

· Additional information:
The content of Benzene (EINECS-Nr. 200-753-7) in the ingredients is less than 0,1% (Note P Annex IA 1272/2008 EU), so the classification as carcinogen need not to apply.
For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures
· After inhalation: In case of unconsciousness place patient stably in side position for transportation.

· After skin contact: Immediately wash with water and soap and rinse thoroughly.

(Contd. on page 3)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 15.05.2023

Version number 3 (replaces version 2)

Revision: 30.03.2022

Trade name: NICRO 203 MOULD RELEASE AGENT 400 ML (Aerosol)

(Contd. of page 2)

- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** Drink plenty of water and provide fresh air. Call for a doctor immediately.
- **4.2 Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **5.2 Special hazards arising from the substance or mixture**
During heating or in case of fire poisonous gases are produced.
- **5.3 Advice for firefighters -**
- **Protective equipment:** Mouth respiratory protective device.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Ensure adequate ventilation
Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.
Keep away from ignition sources.
- **6.2 Environmental precautions:**
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Dispose contaminated material as waste according to section 13.
Ensure adequate ventilation.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
No special measures required.
- **Information about fire - and explosion protection:**
Do not spray onto a naked flame or any incandescent material.
Keep ignition sources away - Do not smoke.
Keep respiratory protective device available.
Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Observe official regulations on storing packagings with pressurised containers.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep container tightly sealed.
- **Storage class:** 2 B

(Contd. on page 4)

GB

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 15.05.2023

Version number 3 (replaces version 2)

Revision: 30.03.2022

Trade name: **NICRO 203 MOULD RELEASE AGENT 400 ML (Aerosol)**

(Contd. of page 3)

· **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· **Ingredients with limit values that require monitoring at the workplace:**

109-87-5 dimethoxymethane

WEL	Short-term value: 3950 mg/m ³ , 1250 ppm
	Long-term value: 3160 mg/m ³ , 1000 ppm

124-38-9 carbon dioxide

WEL	Short-term value: 27400 mg/m ³ , 15000 ppm
	Long-term value: 9150 mg/m ³ , 5000 ppm

· **Additional information:** The lists valid during the making were used as basis.

· 8.2 Exposure controls

· **Appropriate engineering controls** No further data; see section 7.· **Individual protection measures, such as personal protective equipment**· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

· **Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Filter A2/P3

· **Hand protection**

Protective gloves

· **Material of gloves**

Butyl rubber, BR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· **Penetration time of glove material**

Butyl rubber gloves with a thickness of 0.4 mm are resistant to:

Acetone: 480 min

Butyl acetate: 60 min

Ethyl acetate: 170 min

Xylene: 42 min

Butyl rubber gloves with a thickness of 0.4 mm are solvent resistant for 42- 480 minutes. As protective measure, we recommend that users and responsible persons for work safety assume solvent resistance length of 42 minutes. Considering the data in section 3 of this SDS, one can assume longer resistance length in particular cases.

· **Eye/face protection** Not required.

GB

(Contd. on page 5)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 15.05.2023

Version number 3 (replaces version 2)

Revision: 30.03.2022

Trade name: **NICRO 203 MOULD RELEASE AGENT 400 ML (Aerosol)**

(Contd. of page 4)

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

· Physical state	Aerosol
· Colour:	Clear
· Odour:	Solvent-like
· Odour threshold:	Not determined.
· Melting point/freezing point:	Undetermined.
· Boiling point or initial boiling point and boiling range	Not applicable, as aerosol.
· Flammability	Not applicable.
· Lower and upper explosion limit	
· Lower:	0.6 Vol % (Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane)
· Upper:	19.9 Vol % (109-87-5 dimethoxymethane)
· Flash point:	-18 °C (-0.4 °F)
	Not applicable, as aerosol.
· Auto-ignition temperature:	>200 °C (>392 °F)
· Decomposition temperature:	Not determined.
· pH	Mixture is non-soluble (in water).
· Viscosity:	
· Kinematic viscosity	Not determined.
· Dynamic:	Not determined.
· Solubility	
· water:	Not miscible or difficult to mix.
· Partition coefficient n-octanol/water (log value)	Not determined.
· Vapour pressure at 20 °C (68 °F):	5500 hPa (4125.3 mm Hg)
· Density and/or relative density	
· Density at 20 °C (68 °F):	0.8 g/cm ³ (6.7 lbs/gal)
· Relative density	Not determined.
· Vapour density	Not determined.

9.2 Other information

· Appearance:	
· Form:	Aerosol
· Important information on protection of health and environment, and on safety.	
· Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Solvent content:	
· Organic solvents:	90.3 %
· VOC (EC)	---
	810.5 g/l
· VOC-EU%	90.27 %
· Solids content:	0.9 %
· Change in condition	
· Evaporation rate	Not applicable.

Information with regard to physical hazard classes

· Explosives	Void
· Flammable gases	Void
· Aerosols	Extremely flammable aerosol. Pressurised container: May burst if heated.
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Void
· Flammable solids	Void

(Contd. on page 6)

GB

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 15.05.2023

Version number 3 (replaces version 2)

Revision: 30.03.2022

Trade name: NICRO 203 MOULD RELEASE AGENT 400 ML (Aerosol)

(Contd. of page 5)

· <i>Self-reactive substances and mixtures</i>	Void
· <i>Pyrophoric liquids</i>	Void
· <i>Pyrophoric solids</i>	Void
· <i>Self-heating substances and mixtures</i>	Void
· <i>Substances and mixtures, which emit flammable gases in contact with water</i>	Void
· <i>Oxidising liquids</i>	Void
· <i>Oxidising solids</i>	Void
· <i>Organic peroxides</i>	Void
· <i>Corrosive to metals</i>	Void
· <i>Desensitised explosives</i>	Void

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· **LD/LC50 values relevant for classification:**

109-87-5 dimethoxymethane

Oral	LD50	6423 mg/kg (rat)
Dermal	LD50	>5000 mg/kg (rab) (OECD 402)
	LC50 / 96 h	>1000 mg/l (fish) (<i>Oncorhynchus mykiss</i>)

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

Oral	LD50	>5840 mg/kg (rat)
Dermal	LD50	>2920 mg/kg (rab)
Inhalative	LC50 / 4h	>25.2 mg/l (rat)

- **Skin corrosion/irritation** Causes skin irritation.
- **Serious eye damage/irritation** No irritating effect.
- **Respiratory or skin sensitisation** No sensitising effects known.
- **11.2 Information on other hazards**

· **Endocrine disrupting properties**

None of the ingredients is listed.

SECTION 12: Ecological information

· **12.1 Toxicity**

· **Aquatic toxicity:**

109-87-5 dimethoxymethane

EC50 / 48 h	>1200 mg/l (<i>daphnia magna</i>) (<i>Daphnia magna</i>)
-------------	--------------------------------------------------------------

(Contd. on page 7)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 15.05.2023

Version number 3 (replaces version 2)

Revision: 30.03.2022

Trade name: NICRO 203 MOULD RELEASE AGENT 400 ML (Aerosol)

(Contd. of page 6)

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

EC50 / 48 h 3 mg/l (daphnia magna)

EC50 / 72 h 30-100 mg/l (algae)


LC50 / 96 h 11.4 mg/l (fish)

- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Endocrine disrupting properties**
The product does not contain substances with endocrine disrupting properties.
- **12.7 Other adverse effects**
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
Harmful to aquatic organisms

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:**
Disposal must be made according to official regulations.
Disposal must be made according to official regulations.

SECTION 14: Transport information

- **14.1 UN number or ID number**
- **ADR, IMDG, IATA** UN1950
- **14.2 UN proper shipping name**
- **ADR** 1950 AEROSOLS
- **IMDG** AEROSOLS
- **IATA** AEROSOLS, flammable
- **14.3 Transport hazard class(es)**
- **ADR**
- 
- **Class** 2 5F Gases.

(Contd. on page 8)

GB

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 15.05.2023

Version number 3 (replaces version 2)

Revision: 30.03.2022

Trade name: **NICRO 203 MOULD RELEASE AGENT 400 ML (Aerosol)**

(Contd. of page 7)

· **Label** 2.1· **IMDG, IATA**

· **Class** 2.1 Gases.
· **Label** 2.1

· **14.4 Packing group**
· **ADR, IMDG, IATA** not regulated

· **14.5 Environmental hazards:** Not applicable.

· **14.6 Special precautions for user** Warning: Gases.
· **Hazard identification number (Kemler code):** -
· **EMS Number:** F-D,S-U
· **Stowage Code** SW1 Protected from sources of heat.
SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.
· **Segregation Code** SG69 For AEROSOLS with a maximum capacity of 1 litre:
Segregation as for class 9. Stow "separated from" class 1 except for division 1.4.
For AEROSOLS with a capacity above 1 litre:
Segregation as for the appropriate subdivision of class 2.
For WASTE AEROSOLS:
Segregation as for the appropriate subdivision of class 2.

· **14.7 Maritime transport in bulk according to IMO instruments** Not applicable.

· **Transport/Additional information:**

· **ADR**
· **Limited quantities (LQ)** 1L
· **Excepted quantities (EQ)** Code: E0
Not permitted as Excepted Quantity
· **Transport category** 2
· **Tunnel restriction code** D

· **IMDG**
· **Limited quantities (LQ)** 1L
· **Excepted quantities (EQ)** Code: E0
Not permitted as Excepted Quantity
Code: E0
Not permitted as Excepted Quantity

· **UN "Model Regulation":** UN 1950 AEROSOLS, 2.1

GB

(Contd. on page 9)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 15.05.2023

Version number 3 (replaces version 2)

Revision: 30.03.2022

Trade name: NICRO 203 MOULD RELEASE AGENT 400 ML (Aerosol)

(Contd. of page 8)

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category P3b** FLAMMABLE AEROSOLS
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 5000 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50000 t
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**
H225 Highly flammable liquid and vapour.
H280 Contains gas under pressure; may explode if heated.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.
- **Department issuing SDS:** R&D legislation and regulatory advisor
- **Contact:** e-mail: sds-nl@european-aerosols.com
- **Abbreviations and acronyms:**
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Aerosol 1: Aerosols – Category 1
Press. Gas (Liq.): Gases under pressure – Liquefied gas
Flam. Liq. 2: Flammable liquids – Category 2
Skin Irrit. 2: Skin corrosion/irritation – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3
- *** Data compared to the previous version altered.**