

16.03.2023

Kit Components

Product code	Description
--------------	-------------

600555	Presto 2K Epoxypachtel 500g
---------------	------------------------------------

Components:

600555A	Presto 2K Epoxypachtel (Komp. A: Spachtelmasse)
600555B	Presto 2K Epoxypachtel (Komp. B: Härter)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 16.03.2023

Version number 12 (replaces version 11)

Revision: 16.03.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

· **Trade name:** Presto 2K Epoxypachtel (Komp. A: Spachtelmasse)

· **Article number:** 600555A

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

1.3 Details of the supplier of the safety data sheet

· **Sector of Use**
SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

SU21 Consumer uses: Private households / general public / consumers

· **Product category** PC9a Coatings and paints, thinners, paint removers

· **Process category** PROC10 Roller application or brushing

· **Application of the substance / the mixture** Knife filler/ Surfacers

1.4 Emergency telephone number:

· **Manufacturer/Supplier:**

European Aerosols GmbH*

Kurt Vogelsang Strasse 6

D-74855 Haßmersheim

Tel.: +49 (0) 6266 750

e-mail: sds-de@european-aerosols.com

*Formerly known as Motip Dupli GmbH

· **Further information obtainable from:** Department Product Safety

1.4 Emergency telephone number:

Tel.: +49 6266-75-310

Fax +49 6266-75-362

(Mo - Th 08:00 am - 04:00 pm, Fr 08:00 am - 00:30 pm)

UK:

Public emergency phone no: 111

Only for healthcare professionals: 0344 892 0111

Ireland:

Poison center if child has been poisoned: 01 809 2166 (8:00 am - 10:00 pm, 7 days)

Only for healthcare professionals: 01 809 2566 (24 h / 7 days)

Tox Info Suisse 145 (24-h-emergency number)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

· **Classification according to Regulation (EC) No 1272/2008**



environment

Aquatic Chronic 2 H411 Toxic to aquatic life with long lasting effects.



Skin Irrit. 2

H315 Causes skin irritation.

Eye Irrit. 2

H319 Causes serious eye irritation.

(Contd. on page 2)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 16.03.2023

Version number 12 (replaces version 11)

Revision: 16.03.2023

Trade name: Presto 2K Epoxypachtel (Komp. A: Spachtelmasse)

(Contd. of page 1)

Skin Sens. 1 H317 May cause an allergic skin reaction.

2.2 Label elements**Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms

GHS07 GHS09

Signal word Warning**Hazard-determining components of labelling:**reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700)

formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol

2,2'-[hexan-1,6-diylbis(oxy-methylen)]dioxiran

Oxiran, Mono- [(C13-15-alkyloxy) methyl] derivate

fatty acids

Hazard statements

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.

P363 Wash contaminated clothing before reuse.

P501 Dispose of contents / container in accordance with regional regulations.

Additional information:

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

2.3 Other hazards**Results of PBT and vPvB assessment****PBT:** Not applicable.**vPvB:** Not applicable.**SECTION 3: Composition/information on ingredients****3.2 Mixtures****Description:** Mixture of substances listed below with nonhazardous additions.**Dangerous components:**

CAS: 25068-38-6 NLP: 500-033-5 Index number: 603-074-00-8 Reg.nr.: 01-2119456619-26	reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) ⚠ Aquatic Chronic 2, H411 ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317 EUH205 Specific concentration limits: Skin Irrit. 2; H315: C ≥ 5 % Eye Irrit. 2; H319: C ≥ 5 %	20-<25%
CAS: 9003-36-5 NLP: 500-006-8 Reg.nr.: 01-2119454392-40	formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol ⚠ Aquatic Chronic 2, H411 ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	5-<10%

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 16.03.2023

Version number 12 (replaces version 11)

Revision: 16.03.2023

Trade name: Presto 2K Epoxyspachtel (Komp. A: Spachtelmasse)

(Contd. of page 2)

CAS: 13463-67-7 EINECS: 236-675-5 Index number: 022-006-00-2 Reg.nr.: 01-2119489379-17	titanium dioxide ☠ Carc. 2, H351	2.5-<5%
CAS: 933999-84-9 EC number: 618-939-5 Reg.nr.: 01-2119463471-41	2,2'-[hexan-1,6-diylbis(oxy)methylen)]dioxiran ⚠ Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317 Aquatic Chronic 3, H412	2.5-<5%
EC number: 939-183-5 Reg.nr.: 01-2119962192-39	Oxiran, Mono- [(C13-15-alkyloxy) methyl] derivate ⚠ Aquatic Chronic 2, H411 ⚠ Skin Sens. 1, H317	2.5-<5%
CAS: 147900-93-4 EC number: 604-612-4 Reg.nr.: 01-2119971821-33	fatty acids ☠ STOT RE 2, H373 ⚠ Aquatic Chronic 2, H411 ⚠ Acute Tox. 4, H302; Skin Sens. 1, H317	≤0.5%

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact: Immediately wash with water and soap and rinse thoroughly.

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.

· 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

· Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.

· 5.2 Special hazards arising from the substance or mixture

No further relevant information available.

No further relevant information available.

· 5.3 Advice for firefighters -

· Protective equipment: No special measures required.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

(Contd. on page 4)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 16.03.2023

Version number 12 (replaces version 11)

Revision: 16.03.2023

Trade name: Presto 2K Epoxyspachtel (Komp. A: Spachtelmasse)

(Contd. of page 3)

See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling** No special measures required.
- **Information about fire - and explosion protection:** No special measures required.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep container tightly sealed.
- **Storage class:** 10
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· **Ingredients with limit values that require monitoring at the workplace:**

13463-67-7 titanium dioxide

WEL	Long-term value: 10* 4** mg/m ³
	*total inhalable **respirable

· **Additional information:** The lists valid during the making were used as basis.

· 8.2 Exposure controls

- **Appropriate engineering controls** No further data; see item 7.
- **Individual protection measures, such as personal protective equipment**
- **General protective and hygienic measures:**
- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing
- Wash hands before breaks and at the end of work.
- Avoid contact with the eyes and skin.
- Avoid contact with the eyes.
- **Respiratory protection:** Not necessary if room is well-ventilated.
- **Hand protection**



Protective gloves

· **Material of gloves**

Butyl rubber, BR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· **Penetration time of glove material**

Butyl rubber gloves with a thickness of 0.4 mm are resistant to:

Acetone: 480 min

Butyl acetate: 60 min

Ethyl acetate: 170 min

Xylene: 42 min

Butyl rubber gloves with a thickness of 0.4 mm are solvent resistant for 42- 480 minutes. As protective measure, we recommend that users and responsible persons for work safety assume solvent resistance length of 42 minutes. Considering the data in section 3 of this SDS, one can assume longer resistance length in particular cases.

(Contd. on page 5)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 16.03.2023

Version number 12 (replaces version 11)

Revision: 16.03.2023

Trade name: Presto 2K Epoxypachtel (Komp. A: Spachtelmasse)

(Contd. of page 4)

· Eye/face protection



Tightly sealed goggles

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Physical state

Fluid

· Colour:

White

· Odour:

Characteristic

· Odour threshold:

Not determined.

· Melting point/freezing point:

Undetermined.

· Boiling point or initial boiling point and boiling range

>200 °C (>392 °F)

· Flammability

Not applicable.

· Lower and upper explosion limit

· Lower:

Not determined.

· Upper:

Not determined.

· Flash point:

>100 °C (>212 °F) (25068-38-6 reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700))

· Decomposition temperature:

Not determined.

· pH

Not determined.

· Viscosity:

· Kinematic viscosity

Not determined.

· Dynamic at 20 °C (68 °F):

8000-11000 mPas

· Solubility

· water:

Not miscible or difficult to mix.

· Partition coefficient n-octanol/water (log value)

Not determined.

· Density and/or relative density

· Density at 20 °C (68 °F):

1.8 g/cm³ (15 lbs/gal)

· Relative density

Not determined.

· Vapour density

Not determined.

· 9.2 Other information

· Appearance:

· Form:

Pasty

· Important information on protection of health and environment, and on safety.

· Explosive properties:

Product does not present an explosion hazard.

· Solvent content:

· VOC (EC)

0.0 g/l

· VOC-EU%

0.00 %

· Solids content:

58.5 %

· Change in condition

· Evaporation rate

Not determined.

· Information with regard to physical hazard classes

· Explosives

Void

· Flammable gases

Void

· Aerosols

Void

· Oxidising gases

Void

· Gases under pressure

Void

(Contd. on page 6)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 16.03.2023

Version number 12 (replaces version 11)

Revision: 16.03.2023

Trade name: Presto 2K Epoxyspachtel (Komp. A: Spachtelmasse)

(Contd. of page 5)

· Flammable liquids	Void
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flammable gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

*

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.
- **Skin corrosion/irritation** Causes skin irritation.
- **Serious eye damage/irritation** Causes serious eye irritation.
- **Respiratory or skin sensitisation** May cause an allergic skin reaction.
- **11.2 Information on other hazards**

· Endocrine disrupting properties
--

None of the ingredients is listed.

*

SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Endocrine disrupting properties**
The product does not contain substances with endocrine disrupting properties.
- **12.7 Other adverse effects**
- **Remark:** Toxic for fish
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.

(Contd. on page 7)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 16.03.2023

Version number 12 (replaces version 11)

Revision: 16.03.2023

Trade name: Presto 2K Epoxypachtel (Komp. A: Spachtelmasse)

(Contd. of page 6)

Also poisonous for fish and plankton in water bodies.
Toxic for aquatic organisms

SECTION 13: Disposal considerations

· **13.1 Waste treatment methods**

· **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· **Uncleaned packaging:**

· **Recommendation:**

Disposal must be made according to official regulations.

Disposal must be made according to official regulations.

SECTION 14: Transport information

· **14.1 UN number or ID number**

· **ADR, IMDG, IATA**

UN3082

· **14.2 UN proper shipping name**

· **ADR**

3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700), formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol)

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700), formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol), MARINE POLLUTANT


ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700), formaldehyde, oligomeric reaction products with 1-chloro-2,3-epoxypropane and phenol)

· **IMDG**

· **IATA**

· **14.3 Transport hazard class(es)**

· **ADR**



· **Class**

9 (M6) Miscellaneous dangerous substances and articles.

· **Label**

9

· **IMDG**



· **Class**

9 Miscellaneous dangerous substances and articles.

(Contd. on page 8)

GB

Safety data sheet
according to 1907/2006/EC, Article 31


Printing date 16.03.2023

Version number 12 (replaces version 11)

Revision: 16.03.2023

Trade name: Presto 2K Epoxypachtel (Komp. A: Spachtelmasse)

(Contd. of page 7)

· Label	9
· IATA	
	
· Class	9 Miscellaneous dangerous substances and articles.
· Label	9
· 14.4 Packing group	
· ADR, IMDG, IATA	III
· 14.5 Environmental hazards:	
· Marine pollutant:	Yes
· Special marking (ADR):	Symbol (fish and tree)
· Special marking (IATA):	Symbol (fish and tree)
· 14.6 Special precautions for user	Warning: Miscellaneous dangerous substances and articles.
· Hazard identification number (Kemler code):	90
· EMS Number:	F-A,S-F
· Stowage Category	A
· 14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· Transport category	3
· Tunnel restriction code	(-)
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (REACTION PRODUCT: BISPHENOL-A-(EPICHLORHYDRIN); EPOXY RESIN (NUMBER AVERAGE MOLECULAR WEIGHT ≤ 700), FORMALDEHYDE, OLIGOMERIC REACTION PRODUCTS WITH 1-CHLORO-2,3-EPOXYPROPANE AND PHENOL), 9, III

*

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category E2** Hazardous to the Aquatic Environment
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 200 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t

(Contd. on page 9)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 16.03.2023

Version number 12 (replaces version 11)

Revision: 16.03.2023

Trade name: Presto 2K Epoxypachtel (Komp. A: Spachtelmasse)

(Contd. of page 8)

· **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

- H302 Harmful if swallowed.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H351 Suspected of causing cancer.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H411 Toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.
- EUH205 Contains epoxy constituents. May produce an allergic reaction.

· **Abbreviations and acronyms:**

- RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
- IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)
- ICAO: International Civil Aviation Organisation
- ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonised System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- VOC: Volatile Organic Compounds (USA, EU)
- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative
- Acute Tox. 4: Acute toxicity – Category 4
- Skin Irrit. 2: Skin corrosion/irritation – Category 2
- Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
- Skin Sens. 1: Skin sensitisation – Category 1
- Carc. 2: Carcinogenicity – Category 2
- STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
- Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2
- Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

· *** Data compared to the previous version altered.**

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 16.03.2023

Version number 12 (replaces version 11)

Revision: 15.03.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· **Trade name:** Presto 2K Epoxypachtel (Komp. B: Härter)

· **Article number:** 600555B

· 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Sector of Use

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

· **Product category** PC9b Fillers, putties, plasters, modelling clay

· **Process category** PROC10 Roller application or brushing

· **Application of the substance / the mixture** Hardening agent/ Curing agent

· 1.3 Details of the supplier of the safety data sheet

· **Manufacturer/Supplier:**

European Aerosols GmbH*

Kurt Vogelsang Strasse 6

D-74855 Haßmersheim

Tel.: +49 (0) 6266 750

e-mail: sds-de@european-aerosols.com

*Formerly known as Motip Dupli GmbH

· **Further information obtainable from:** Department Product Safety

· 1.4 Emergency telephone number:

Tel.: +49 6266-75-310

Fax +49 6266-75-362

(Mo - Th 08:00 am - 04:00 pm, Fr 08:00 am - 00:30 pm)

UK:

Public emergency phone no: 111

Only for healthcare professionals: 0344 892 0111

Ireland:

Poison center if child has been poisoned: 01 809 2166 (8:00 am - 10:00 pm, 7 days)

Only for healthcare professionals: 01 809 2566 (24 h / 7 days)

Tox Info Suisse 145 (24-h-emergency number)

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

· **Classification according to Regulation (EC) No 1272/2008**



corrosion

Skin Corr. 1B

H314 Causes severe skin burns and eye damage.

Eye Dam. 1

H318 Causes serious eye damage.



(Contd. on page 2)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 16.03.2023

Version number 12 (replaces version 11)

Revision: 15.03.2023

Trade name: Presto 2K Epoxypachtel (Komp. B: Härter)

(Contd. of page 1)

Skin Sens. 1 H317 May cause an allergic skin reaction.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

2.2 Label elements**Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms

GHS05 GHS07

Signal word Danger**Hazard-determining components of labelling:**

3-aminomethyl-3,5,5-trimethylcyclohexylamine

m-phenylenebis(methylamine)

phenol, styrenated

N-(3-(trimethoxysilyl)propyl)ethylenediamine

fatty acids

Hazard statements

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P280 Wear protective gloves / eye protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P405 Store locked up.

P501 Dispose of contents / container in accordance with regional regulations.

Additional information:

EUH212 Warning! Hazardous respirable dust may be formed when used. Do not breathe dust.

2.3 Other hazards**Results of PBT and vPvB assessment****PBT:** Not applicable.**vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Mixtures**Description:** Mixture of substances listed below with nonhazardous additions.**Dangerous components:**

CAS: 100-51-6	Benzyl alcohol	5-<10%
EINECS: 202-859-9	⚠ Acute Tox. 4, H302; Acute Tox. 4, H332; Eye Irrit. 2, H319	
Index number: 603-057-00-5		
Reg.nr.: 01-2119492630-38		

(Contd. on page 3)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 16.03.2023

Version number 12 (replaces version 11)

Revision: 15.03.2023

Trade name: Presto 2K Epoxyspachtel (Komp. B: Härter)

(Contd. of page 2)

CAS: 1477-55-0 EINECS: 216-032-5 Reg.nr.: 01-2119480150-50	<i>m</i> -phenylenebis(methylamine) ⚠ Skin Corr. 1B, H314 ⚠ Acute Tox. 4, H332; Skin Sens. 1, H317 Aquatic Chronic 3, H412	5-<10%
CAS: 2855-13-2 EINECS: 220-666-8 Index number: 612-067-00-9 Reg.nr.: 01-2119514687-32	3-aminomethyl-3,5,5-trimethylcyclohexylamine ⚠ Skin Corr. 1B, H314; Eye Dam. 1, H318 ⚠ Acute Tox. 4, H302; Skin Sens. 1A, H317 ATE: LD50 oral: 1030 mg/kg Specific concentration limit: Skin Sens. 1A; H317: C ≥ 0.001 %	5-<10%
CAS: 61788-44-1	phenol, styrenated ⚠ Aquatic Chronic 2, H411 ⚠ Skin Irrit. 2, H315; Skin Sens. 1, H317	2.5-<5%
CAS: 13463-67-7 EINECS: 236-675-5 Reg.nr.: 01-2119489379-17	titanium dioxide substance with a Community workplace exposure limit	<2.5%
CAS: 1760-24-3 EINECS: 217-164-6 Reg.nr.: 01-2119970215-39	N-(3-(trimethoxysilyl)propyl)ethylenediamine ⚠ STOT RE 2, H373 ⚠ Skin Corr. 1B, H314; Eye Dam. 1, H318 ⚠ Skin Sens. 1, H317; STOT SE 3, H335	≤0.5%
CAS: 147900-93-4 EC number: 604-612-4 Reg.nr.: 01-2119971821-33	fatty acids ⚠ STOT RE 2, H373 ⚠ Aquatic Chronic 2, H411 ⚠ Acute Tox. 4, H302; Skin Sens. 1, H317	≤0.5%

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:**
Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:** Drink plenty of water and provide fresh air. Call for a doctor immediately.
- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents:** Use fire extinguishing methods suitable to surrounding conditions.
- **5.2 Special hazards arising from the substance or mixture**
No further relevant information available.
No further relevant information available.
- **5.3 Advice for firefighters -**
- **Protective equipment:** No special measures required.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 16.03.2023

Version number 12 (replaces version 11)

Revision: 15.03.2023

Trade name: Presto 2K Epoxypachtel (Komp. B: Härter)

(Contd. of page 3)

- **6.2 Environmental precautions:**
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Use neutralising agent.
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Thorough dedusting.
No special measures required.
- **Information about fire - and explosion protection:** No special measures required.
- **7.2 Conditions for safe storage, including any incompatibilities**
· **Storage:**
· **Requirements to be met by storerooms and receptacles:** No special requirements.
· **Information about storage in one common storage facility:** Not required.
· **Further information about storage conditions:** Keep container tightly sealed.
- **Storage class:** 8 A
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· **Ingredients with limit values that require monitoring at the workplace:**

13463-67-7 titanium dioxide

WEL	Long-term value: 10* 4** mg/m ³ *total inhalable **respirable
-----	---

- **Additional information:** The lists valid during the making were used as basis.

· 8.2 Exposure controls

- **Appropriate engineering controls** No further data; see item 7.
- **Individual protection measures, such as personal protective equipment**
- **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Avoid contact with the eyes and skin.
Avoid contact with the eyes.
- **Respiratory protection:** Not necessary if room is well-ventilated.
- **Hand protection**



Protective gloves

· **Material of gloves**

Butyl rubber, BR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· **Penetration time of glove material**

Butyl rubber gloves with a thickness of 0.4 mm are resistant to:

Acetone: 480 min

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 16.03.2023

Version number 12 (replaces version 11)

Revision: 15.03.2023

Trade name: Presto 2K Epoxypachtel (Komp. B: Härter)

(Contd. of page 4)

Butyl acetate: 60 min

Ethyl acetate: 170 min

Xylene: 42 min

Butyl rubber gloves with a thickness of 0.4 mm are solvent resistant for 42- 480 minutes. As protective measure, we recommend that users and responsible persons for work safety assume solvent resistance length of 42 minutes. Considering the data in section 3 of this SDS, one can assume longer resistance length in particular cases.

· **Eye/face protection**



Tightly sealed goggles

SECTION 9: Physical and chemical properties

· **9.1 Information on basic physical and chemical properties**

· **General Information**

· Physical state	Solid
· Colour:	Grey
· Odour:	Characteristic
· Odour threshold:	Not determined.
· Melting point/freezing point:	Undetermined.
· Boiling point or initial boiling point and boiling range	Undetermined.
· Flammability	Not determined.
· Lower and upper explosion limit	
· Lower:	Not determined.
· Upper:	Not determined.
· Flash point:	101 °C (213.8 °F) (100-51-6 Benzyl alcohol)
· Decomposition temperature:	Not determined.
· pH	Mixture is non-soluble (in water).
· Viscosity:	
· Kinematic viscosity	Not applicable.
· Dynamic:	Not applicable.
· Solubility	
· water:	Not miscible or difficult to mix.
· Partition coefficient n-octanol/water (log value)	Not determined.
· Vapour pressure:	Not applicable.
· Density and/or relative density	
· Density at 20 °C (68 °F):	2 g/cm ³ (16.7 lbs/gal)
· Relative density	Not determined.
· Vapour density	Not applicable.

· **9.2 Other information**

· Appearance:	
· Form:	Pasty
· Important information on protection of health and environment, and on safety.	
· Explosive properties:	Product does not present an explosion hazard.
· Solvent content:	
· Organic solvents:	9.0 %
· VOC (EC)	---
· VOC-EU%	
· Solids content:	100.0 %
· Change in condition	
· Evaporation rate	Not applicable.

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 16.03.2023

Version number 12 (replaces version 11)

Revision: 15.03.2023

Trade name: Presto 2K Epoxypachtel (Komp. B: Härter)

(Contd. of page 5)

- | | |
|--|------|
| · Information with regard to physical hazard classes | |
| · Explosives | Void |
| · Flammable gases | Void |
| · Aerosols | Void |
| · Oxidising gases | Void |
| · Gases under pressure | Void |
| · Flammable liquids | Void |
| · Flammable solids | Void |
| · Self-reactive substances and mixtures | Void |
| · Pyrophoric liquids | Void |
| · Pyrophoric solids | Void |
| · Self-heating substances and mixtures | Void |
| · Substances and mixtures, which emit flammable gases in contact with water | Void |
| · Oxidising liquids | Void |
| · Oxidising solids | Void |
| · Organic peroxides | Void |
| · Corrosive to metals | Void |
| · Desensitised explosives | Void |

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· **LD/LC50 values relevant for classification:**

100-51-6 Benzyl alcohol

Inhalative	LC50 / 4h	4.178 mg/l (rat)
------------	-----------	------------------

2855-13-2 3-aminomethyl-3,5,5-trimethylcyclohexylamine

Oral	LD50	1030 mg/kg (ATE)
------	------	------------------

- **Skin corrosion/irritation** Causes severe skin burns and eye damage.
- **Serious eye damage/irritation** Causes serious eye damage.
- **Respiratory or skin sensitisation** May cause an allergic skin reaction.
- **11.2 Information on other hazards**

· **Endocrine disrupting properties**

61788-44-1	phenol, styrenated
------------	--------------------

List II

SECTION 12: Ecological information

- **12.1 Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.

(Contd. on page 7)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 16.03.2023

Version number 12 (replaces version 11)

Revision: 15.03.2023

Trade name: Presto 2K Epoxypachtel (Komp. B: Härter)



(Contd. of page 6)

- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Endocrine disrupting properties** For information on endocrine disrupting properties see section 11.
- **12.7 Other adverse effects**
- **Remark:** Harmful to fish
- **Additional ecological information:**
- **General notes:**
 Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
 Do not allow product to reach ground water, water course or sewage system.
 Must not reach sewage water or drainage ditch undiluted or unneutralised.
 Danger to drinking water if even small quantities leak into the ground.
 Harmful to aquatic organisms

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**
 Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:**
 Disposal must be made according to official regulations.
 Disposal must be made according to official regulations.

SECTION 14: Transport information

- | | |
|--|---|
| · 14.1 UN number or ID number | |
| · ADR, IMDG, IATA | UN1759 |
| · 14.2 UN proper shipping name | |
| · ADR | 1759 CORROSIVE SOLID, N.O.S. (m-phenylenebis(methylamine), ISOPHORONEDIAMINE) |
| · IMDG, IATA | CORROSIVE SOLID, N.O.S. (m-phenylenebis(methylamine), ISOPHORONEDIAMINE) |
| · 14.3 Transport hazard class(es) | |
| · ADR | |
| |  |
| · Class | 8 (C10) Corrosive substances. |
| · Label | 8 |
| · IMDG, IATA | |
| |  |
| · Class | 8 Corrosive substances. |
| · Label | 8 |
| · 14.4 Packing group | |
| · ADR, IMDG, IATA | II |

(Contd. on page 8)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 16.03.2023

Version number 12 (replaces version 11)

Revision: 15.03.2023

Trade name: Presto 2K Epoxypachtel (Komp. B: Härter)

(Contd. of page 7)

· 14.5 Environmental hazards:	Not applicable.
· 14.6 Special precautions for user	Warning: Corrosive substances.
· Hazard identification number (Kemler code):	80
· EMS Number:	F-A,S-B
· Stowage Category	A
· 14.7 Maritime transport in bulk according to IMO instruments	Not applicable.
· Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	1 kg
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 g Maximum net quantity per outer packaging: 500 g
· Transport category	2
· Tunnel restriction code	E
· IMDG	
· Limited quantities (LQ)	1 kg
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 g Maximum net quantity per outer packaging: 500 g
· UN "Model Regulation":	UN 1759 CORROSIVE SOLID, N.O.S. (M-PHENYLENEBIS(METHYLAMINE), ISOPHORONEDIAMINE), 8, II

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**
H302 Harmful if swallowed.
H314 Causes severe skin burns and eye damage.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.
H373 May cause damage to organs through prolonged or repeated exposure.
H411 Toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.
- **Abbreviations and acronyms:**
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonised System of Classification and Labelling of Chemicals

(Contd. on page 9)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 16.03.2023

Version number 12 (replaces version 11)

Revision: 15.03.2023

Trade name: Presto 2K Epoxypachtel (Komp. B: Härter)

(Contd. of page 8)

*EINECS: European Inventory of Existing Commercial Chemical Substances**ELINCS: European List of Notified Chemical Substances**CAS: Chemical Abstracts Service (division of the American Chemical Society)**VOC: Volatile Organic Compounds (USA, EU)**LC50: Lethal concentration, 50 percent**LD50: Lethal dose, 50 percent**PBT: Persistent, Bioaccumulative and Toxic**vPvB: very Persistent and very Bioaccumulative**Acute Tox. 4: Acute toxicity – Category 4**Skin Corr. 1B: Skin corrosion/irritation – Category 1B**Skin Irrit. 2: Skin corrosion/irritation – Category 2**Eye Dam. 1: Serious eye damage/eye irritation – Category 1**Eye Irrit. 2: Serious eye damage/eye irritation – Category 2**Skin Sens. 1: Skin sensitisation – Category 1**Skin Sens. 1A: Skin sensitisation – Category 1A**STOT SE 3: Specific target organ toxicity (single exposure) – Category 3**STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2**Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2**Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3*

GB