

Page 1/10

*

*

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 15.05.2023

Version number 15 (replaces version 14)

Revision: 30.03.2022

1.1 Product iden	tifier
	CRO 920 FOAM CLEANER PLUS 500 ML (AEROSOL)
No further releved Sector of Use SU21 Consume SU22 Professio Product category PROC7 Industr PROC11 Non in	ntified uses of the substance or mixture and uses advised against ant information available. r uses: Private households / general public / consumers nal uses: Public domain (administration, education, entertainment, services, craftsmen) of Flux agents for casting
Manufacturer/S European Aeross Wolfraamweg 2 NL-8471 XC Wo The Netherlands Tel : +31 (0)561 e-mail: sds-nl@e *Formerly know. Further informa 1.4 Emergency t +31 (0)561-6944	vls B.V.* Ivega
UK: NPIS Nation	al Polsons Information Centre Tel: +44 0544 892 0111
2.1 Classificatio	Hazards identification n of the substance or mixture cording to Regulation (EC) No 1272/2008
Aerosol 1 H22	2-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.
Eye Irrit. 2 H31 STOT SE 3 H33	-

Page 2/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 15.05.2023

Version number 15 (replaces version 14)

Revision: 30.03.2022

Trade name: NICRO 920 FOAM CLEANER PLUS 500 ML (AEROSOL)

(Contd. of page 1) · Hazard pictograms GHS02 GHS07 · Signal word Danger · Hazard-determining components of labelling: propan-2-ol 1-methoxy-2-propanol · Hazard statements H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness. · Precautionary statements P101 If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children. P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 Do not spray on an open flame or other ignition source. P251 Do not pierce or burn, even after use. P260 Do not breathe spray. P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. P501 Dispose of contents / container in accordance with regional regulations. · Additional information: Buildup of explosive mixtures possible without sufficient ventilation. · 2.3 Other hazards · Results of PBT and vPvB assessment

• *PBT:* Not applicable. • *vPvB:* Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

2

 $\cdot \textit{Description: Mixture of substances listed below with nonhazardous additions.}$

· Dangerous components:		
CAS: 67-63-0 EINECS: 200-661-7	propan-2-ol	12.5-<20%
Index number: 603-117-00-0 Reg.nr.: 01-2119457558-25	 Flam. Liq. 2, H225 Eye Irrit. 2, H319; STOT SE 3, H336 	
CAS: 74-98-6 EINECS: 200-827-9 Index number: 601-003-00-5 Reg.nr.: 01-2119486944-21	propane Flam. Gas 1A, H220 Press. Gas (Comp.), H280	2.5-<5%
CAS: 107-98-2 EINECS: 203-539-1 Index number: 603-064-00-3 Reg.nr.: 01-2119457435-35	1-methoxy-2-propanol Flam. Liq. 3, H226 STOT SE 3, H336	2.5-<5%
	(Contd. on page 3)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 15.05.2023

Version number 15 (replaces version 14)

Revision: 30.03.2022

Trade name: NICRO 920 FOAM CLEANER PLUS 500 ML (AEROSOL)

		(Contd. of page 2)
CAS: 106-97-8	butane (containing $< 0,1$ % butadiene (203-450-8))	2.5-<5%
EINECS: 203-448-7	🚸 Flam. Gas 1A, H220	
Index number: 601-004-00-0	Press. Gas (Comp.), H280	
Reg.nr.: 01-2119474691-32		
CAS: 75-28-5	isobutane (containing < 0,1 % butadiene (203-450-8))	2.5-<5%
EINECS: 200-857-2	🚸 Flam. Gas 1A, H220	
Index number: 601-004-00-0	Press. Gas (Comp.), H280	
Reg.nr.: 01-2119485395-27		
CAS: 1336-21-6	ammonia	<i>≤</i> 0.5%
EINECS: 215-647-6	🤣 Skin Corr. 1B, H314; Eye Dam. 1, H318	
Index number: 007-001-01-2		
Reg.nr.: 01-2119982985-14	Specific concentration limit: STOT SE 3; H335: $C \ge 5 \%$	
· Regulation (EC) No 648/200	4 on detergents / Labelling for contents	
aliphatic hydrocarbons		≥ 5 - <15%
• Additional information: For	the wording of the listed hazard phrases refer to section 16.	

SECTION 4: First aid measures

• 4.1 Description of first aid measures

- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Generally the product does not irritate the skin.
- After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.
- \cdot 4.2 Most important symptoms and effects, both acute and delayed
- No further relevant information available.
- \cdot 4.3 Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- \cdot 5.2 Special hazards arising from the substance or mixture
- During heating or in case of fire poisonous gases are produced.
- · 5.3 Advice for firefighters -
- · Protective equipment: Mouth respiratory protective device.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures Ensure adequate ventilation Mount respiratory protective device. Wear protective equipment. Keep unprotected persons away. Keep away from ignition sources.
6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
6.3 Methods and material for containment and cleaning up: Dispose contaminated material as waste according to section 13. Ensure adequate ventilation.
6.4 Reference to other sections See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

(Contd. on page 4)

GB

Page 4/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 15.05.2023

Version number 15 (replaces version 14)

Revision: 30.03.2022

Trade name: NICRO 920 FOAM CLEANER PLUS 500 ML (AEROSOL)

See Section 13 for disposal information.

SECTION 7: Handling and storage

- 7.1 Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
- Information about fire and explosion protection: Do not spray onto a naked flame or any incandescent material. Keep ignition sources away - Do not smoke. Keep respiratory protective device available.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles:
- Observe official regulations on storing packagings with pressurised containers.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 2 B
- 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Ingredient	s with la	imit values that require monitoring at the workplace:
67-63-0 pr	opan-2-	ol
WEL Shor	t-term v	value: 1250 mg/m³, 500 ppm
Long	g-term v	alue: 999 mg/m³, 400 ppm
107-98-21	-metho.	xy-2-propanol
		value: 560 mg/m³, 150 ppm
~	g-term v	alue: 375 mg/m³, 100 ppm
Sk		(202, 450, 0)
		containing < 0,1 % butadiene (203-450-8))
		alue: 1810 mg/m³, 750 ppm alue: 1450 mg/m³, 600 ppm
	,	e than 0.1% of buta-1.3-diene)
· DNELs	(9	
		al
67-63-0 pr	-	
Oral		26 mg/kg /per day (Consumer, longterm systemic)
Dermal		888 mg/kg /per day (Worker, longterm systemic)
		319 mg/kg /per day (Consumer, longterm systemic)
Inhalative	DNEL	500 mg/m3 (Worker, longterm systemic)
	DNEL	89 mg/m3 (Consumer, longterm systemic)
107-98-21	-metho.	xy-2-propanol
Oral	DNEL	3.3 mg/kg /per day (Consumer, longterm systemic)
Dermal	DNEL	50.6 mg/kg /per day (Worker, longterm systemic)
	DNEL	18.1 mg/kg /per day (Consumer, longterm systemic)
Inhalative	DNEL	553.5 mg/m3 (Worker, acute local)
	DNEL	369 mg/m3 (Worker, longterm systemic)
	DNEL	43.9 mg/m3 (Consumer, longterm systemic)
		(Contd. on page 5)
		GB

(Contd. of page 3)

Page 5/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 15.05.2023

particular cases.

Version number 15 (replaces version 14)

Revision: 30.03.2022

Trade name: NICRO 920 FOAM CLEANER PLUS 500 ML (AEROSOL)

	(Contd. of page 4)
Γ	· PNECs
Γ	67-63-0 propan-2-ol
	PNEC 140.9 mg/l (Freshwater)
	PNEC 140.9 mg/l (Seawater)
	PNEC 140.9 mg/l (Sporadic release)
	PNEC 2251 mg/l (Sewage treatment plant)
	PNEC 552 mg/kg (Freshwater sediment)
	PNEC 552 mg/kg (Seawater sediment)
F	107-98-2 1-methoxy-2-propanol
F	PNEC 10 mg/l (Freshwater)
	PNEC 1 mg/l (Seawater)
	PNEC 100 mg/l (Sporadic release)
	PNEC 100 mg/l (Sewage treatment plant)
	PNEC 52.3 mg/kg (Freshwater sediment)
	PNEC 5.2 mg/kg (Seawater sediment)
	PNEC 4.59 mg/kg (Soil)
L	• Additional information: The lists valid during the making were used as basis.
	•
	• 8.2 Exposure controls • Appropriate engineering controls No further data; see section 7.
	· Individual protection measures, such as personal protective equipment
	• General protective and hygienic measures:
	Keep away from foodstuffs, beverages and feed.
	Immediately remove all soiled and contaminated clothing
	Wash hands before breaks and at the end of work. Do not inhale gases / fumes / aerosols.
	Avoid contact with the eyes and skin.
	Avoid contact with the eyes.
	· Respiratory protection:
	In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
	Filter A2/P3
	· Hand protection
	Protective gloves
	· Material of gloves
	Butyl rubber, BR
	The selection of the suitable gloves does not only depend on the material, but also on further marks of
	quality and varies from manufacturer to manufacturer.
	• Penetration time of glove material Butyl rubber gloves with a thickness of 0.4 mm are resistant to:
	Acetone: 480 min
	Butyl acetate: 60 min
	Ethyl acetate: 170 min
	Xylene: 42 min Butyl rubber gloves with a thickness of 0.4 mm are solvent resistant for 42, 480 minutes. As protective
	Butyl rubber gloves with a thickness of 0.4 mm are solvent resistant for 42- 480 minutes. As protective measure, we recommend that users and responsible persons for work safety assume solvent resistance length of 42 minutes. Considering the data in section 3 of this SDS, one can assume longer resistance length in
	particular cases

(Contd. on page 6)

GB

*

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 15.05.2023

Version number 15 (replaces version 14)

Revision: 30.03.2022

Trade name: NICRO 920 FOAM CLEANER PLUS 500 ML (AEROSOL)

Eye/face protection		(Contd. of page
Tightly sealed goggles		
	<i>,</i> •	
SECTION 9: Physical and chemical propo 9.1 Information on basic physical and chemical p		
General Information	Topernes	
Physical state	Aerosol	
Colour:	Colourless	
Odour:	Ammonia-like	
Odour threshold:	Not determined.	
Melting point/freezing point:	Undetermined.	
Boiling point or initial boiling point and boiling		
range	Not applicable, as aerosol.	
Flammability	Not applicable.	
Lower and upper explosion limit		
Lower:	2 Vol % (67-63-0 propan-2-ol)	
Upper:	12 Vol % (67-63-0 propan-2-ol)	
Flash point:	Not applicable, as aerosol.	
Auto-ignition temperature:	425 °C (797 °F) (67-63-0 propan-2-ol)	
Decomposition temperature:	Not determined.	
<i>pH at 20 °C (68 °F)</i>	10	
Viscosity:		
Kinematic viscosity	Not determined.	
Dynamic:	Not determined.	
Solubility		
water:	Not miscible or difficult to mix.	
Partition coefficient n-octanol/water (log value) Vancur processing at 20 \cdot C (68 \cdot E):	Not determined.	
Vapour pressure at 20 °C (68 °F): Density and/or relative density	3500 hPa (2625.2 mm Hg)	
Density analog relative density Density at 20 C (68 F):	0.9 g/cm ³ (7.5 lbs/gal)	
Relative density	Not determined.	
Vapour density	Not determined.	
	ivoi ueieimineu.	
9.2 Other information		
Appearance:	A 1	
Form: Important information on protection of health and	Aerosol d	
environment, and on safety.	No.4 dot on the d	
Explosive properties:	Not determined.	
Solvent content:	2160/	
Organic solvents:	31.6 % 67.9 %	
Water: VOC (EC)	07.9 % 	
	 740.9 g/l	
VOC-EU%	740.9 g/i 31.60 %	
Solids content:	0.1%	
Change in condition	0.1 /0	
Evaporation rate	Not applicable.	
-		
Information with regard to physical hazard classe	S	

(Contd. on page 7)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 15.05.2023

Version number 15 (replaces version 14)

Revision: 30.03.2022

Trade name: NICRO 920 FOAM CLEANER PLUS 500 ML (AEROSOL)

	(Contd. of page 6)
· Flammable gases	Void
·Aerosols	Extremely flammable aerosol. Pressurised container:
	May burst if heated.
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Void
· Flammable solids	Void
• Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void
· Self-heating substances and mixtures	Void
· Substances and mixtures, which emit flamm	able
gases in contact with water	Void
· Oxidising liquids	Void
· Oxidising solids	Void
· Organic peroxides	Void
· Corrosive to metals	Void
· Desensitised explosives	Void

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- \cdot 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

· 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

· Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50) values	relevant fo	for classification:	
-----------	----------	-------------	---------------------	--

67-63-0 propan-2-ol			
Oral	LD50	5840 mg/kg (rat)	
Dermal	LD50	13900 mg/kg (rabbit)	
Inhalative	LC50	>25 mg/l (rat) LC 50: 6h	
 Serious ey Respirator STOT-sing 	e dama y or sk gle expe	ritation No irritant effect. age/irritation Causes serious eye irritation. in sensitisation No sensitising effects known. osure May cause drowsiness or dizziness. on other hazards	
· Endocrine	· Endocrine disrupting properties		

None of the ingredients is listed.

(Contd. on page 8)

GB

Page 8/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 15.05.2023

Version number 15 (replaces version 14)

Revision: 30.03.2022

Trade name: NICRO 920 FOAM CLEANER PLUS 500 ML (AEROSOL)

(Contd. of page 7)

SECTION 12: Ecological information

- · 12.1 Toxicity
- Aquatic toxicity:
- 67-63-0 propan-2-ol
- LC50/96h 9640 mg/l (pimephales promelas; 96h)

LC50 / 24 h 9714 mg/l (daphnia magna)

· 12.2 Persistence and degradability No further relevant information available.

- 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties
- The product does not contain substances with endocrine disrupting properties.
- \cdot 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation:

*

Disposal must be made according to official regulations. Disposal must be made according to official regulations.

· 14.1 UN number or ID number · ADR, IMDG, IATA	UN1950	
· 14.2 UN proper shipping name		
· ADR	1950 AEROSOLS	
· IMDG	AEROSOLS	
·IATA	AEROSOLS, flammable	
· ADR		

Page 9/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 15.05.2023

Version number 15 (replaces version 14)

Revision: 30.03.2022

Trade name: NICRO 920 FOAM CLEANER PLUS 500 ML (AEROSOL)

Labol	(Contd. of pag
Label	2.1
IMDG, IATA	
2	
Class	2.1 Gases.
Label	2.1
14.4 Packing group	
ADR, IMDĞ, IATA	not regulated
14.5 Environmental hazards:	Not applicable.
14.6 Special precautions for user	Warning: Gases.
Hazard identification number (Kemler code):	-
EMS Number:	F-D,S-U
Segregation groups	(SGG18) Alkalis
Stowage Code	SW1 Protected from sources of heat.
	SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity
	above 1 litre: Category B. For WASTE AEROSOLS:
	Category C, Clear of living quarters.
Segregation Code	SG69 For AEROSOLS with a maximum capacity of 1
Segregation Code	litre:
	Segregation as for class 9. Stow "separated from" cla
	<i>I except for division 1.4.</i>
	<i>For AEROSOLS with a capacity above 1 litre:</i>
	Segregation as for the appropriate subdivision of class
	2.
	For WASTE AEROSOLS:
	Segregation as for the appropriate subdivision of class
	2.
14.7 Maritime transport in bulk according to IM	10
instruments	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	
Excepted quantities (EQ)	Code: E0
T	Not permitted as Excepted Quantity
Transport category	2
Tunnel restriction code	D
IMDG	17
Limited quantities (LQ)	
Excepted quantities (EQ)	Code: E0
	Not permitted as Excepted Quantity
	Code: E0 Not permitted as Excepted Quantity
	ποι ρεπιαιέα αν Επεεριέα Quantity
UN ''Model Regulation'':	UN 1950 AEROSOLS, 2.1

(Contd. on page 10)

Page 10/10

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 15.05.2023

Version number 15 (replaces version 14)

Revision: 30.03.2022

Trade name: NICRO 920 FOAM CLEANER PLUS 500 ML (AEROSOL)

(Contd. of page 9)

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P3a FLAMMABLE AEROSOLS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- $\cdot \tilde{Q}$ ualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H220 Extremely flammable gas.
H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H280 Contains gas under pressure; may explode if heated.
H314 Causes severe skin burns and eye damage.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H400 Very toxic to aquatic life.

- · Department issuing SDS: R&D legislation and regulatory advisor
- · Contact: e-mail: sds-nl@european-aerosols.com

· Abbreviations and acronyms: ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) DNEL: Derived No-Effect Level (UK REACH) PNEC: Predicted No-Effect Concentration (UK REACH) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Gas 1A: Flammable gases - Category 1A Aerosol 1: Aerosols - Category 1 Press. Gas (Comp.): Gases under pressure - Compressed gas Flam. Liq. 2: Flammable liquids - Category 2 Flam. Liq. 3: Flammable liquids - Category 3 Skin Corr. 1B: Skin corrosion/irritation – Category 1B Eye Dam. 1: Serious eye damage/eye irritation - Category 1 Eye Irrit. 2: Serious eye damage/eye irritation - Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1 \cdot * Data compared to the previous version altered.