

Page 1/9

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 30.05.2022 Version number 116 (replaces version 115) Revision: 30.03.2022

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: PRESTO QUICK START 150 ML
- · Article number: 429804
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Sector of Use

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

· Product category

PC0 Other

PC14 Metal surface treatment products

· Process category

PROC7 Industrial spraying

PROC11 Non industrial spraying

- · Application of the substance / the mixture Auxiliary
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

European Aerosols B.V.\*

Wolfraamweg 2

NL-8471 XC Wolvega

The Netherlands

Tel: +31 (0)561 694400

e-mail: sds-nl@european-aerosols.com

- \*Formerly known as Motip Dupli B.V.
- · Further information obtainable from: Department Product Safety
- · 1.4 Emergency telephone number:

+31 (0)561-694400 (09:00h - 17:00h)

UK: NPIS National Poisons Information Centre Tel: +44 0344 892 0111

## SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



Aerosol 1

 ${\it H222-H229}\ Extremely\ flammable\ aerosol.\ Pressurised\ container:\ May\ burst\ if\ heated.$ 



STOT SE 3 H336 May cause drowsiness or dizziness.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

(Contd. on page 2)

Printing date 30.05.2022 Version number 116 (replaces version 115) Revision: 30.03.2022

Trade name: PRESTO QUICK START 150 ML

(Contd. of page 1)

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

· Hazard pictograms





GHS02 GHS07

- · Signal word Danger
- · Hazard-determining components of labelling:

diethyl ether

pentane

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H336 May cause drowsiness or dizziness.

*H412 Harmful to aquatic life with long lasting effects.* 

· Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

*P211* Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P260 Do not breathe spray.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents / container in accordance with regional regulations.

· Additional information:

EUH019 May form explosive peroxides.

EUH066 Repeated exposure may cause skin dryness or cracking.

Buildup of explosive mixtures possible without sufficient ventilation.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

### SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · **Description:** Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 60-29-7	diethyl ether	25-<50%
EINECS: 200-467-2	♠ Flam. Liq. 1, H224	-
Index number: 603-022-00-4	V , , , , ,	
Reg.nr.: 01-2119535785-29	EUH019, EUH066	
CAS: 74-98-6	propane	12.5-<20%
EINECS: 200-827-9	♦ Flam. Gas 1A, H220	
Index number: 601-003-00-5	Press. Gas (Comp.), H280	
Reg.nr.: 01-2119486944-21		
CAS: 109-66-0	pentane	12.5-<20%
EINECS: 203-692-4	<b>(</b> Flam. Liq. 2, H225	
Index number: 601-006-00-1	<b>♦</b> Asp. Tox. 1, H304	
Reg.nr.: 01-2119459286-30	Aquatic Chronic 2, H411	
	♦ STOT SE 3, H336	
	EUH066	

(Contd. on page 3)

Printing date 30.05.2022 Version number 116 (replaces version 115) Revision: 30.03.2022

Trade name: PRESTO QUICK START 150 ML

		(Contd. of page 2
CAS: 106-97-8	butane (containing < 0,1 % butadiene (203-450-8))	10-<12.5%
EINECS: 203-448-7	🅸 Flam. Gas 1A, H220	
Index number: 601-004-00-0	Press. Gas (Comp.), H280	
Reg.nr.: 01-2119474691-32		
CAS: 75-28-5	isobutane (containing < 0,1 % butadiene (203-450-8))	10-<12.5%
EINECS: 200-857-2	🊸 Flam. Gas 1A, H220	
Index number: 601-004-00-0	Press. Gas (Comp.), H280	
Reg.nr.: 01-2119485395-27		

· Additional information: For the wording of the listed hazard phrases refer to section 16.

#### SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.
- · 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

#### SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- · 5.2 Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

- · 5.3 Advice for firefighters -
- · Protective equipment: Mouth respiratory protective device.

### SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

Keep away from ignition sources.

· 6.2 Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

#### SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

(Contd. on page 4)

Printing date 30.05.2022 Version number 116 (replaces version 115) Revision: 30.03.2022

Trade name: PRESTO QUICK START 150 ML

(Contd. of page 3)

· Information about fire - and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Keep respiratory protective device available.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Store in a cool location.

Observe official regulations on storing packagings with pressurised containers.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 2 B
- · 7.3 Specific end use(s) No further relevant information available.

### SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

60-29-7 diethyl ether

WEL Short-term value: 620 mg/m³, 200 ppm Long-term value: 310 mg/m³, 100 ppm

109-66-0 pentane

WEL Long-term value: 1800 mg/m³, 600 ppm

106-97-8 butane (containing < 0,1 % butadiene (203-450-8))

WEL Short-term value: 1810 mg/m³, 750 ppm

Long-term value: 1450 mg/m³, 600 ppm Carc (if more than 0.1% of buta-1.3-diene)

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see item 7.
- · Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

· Respiratory protection:



In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Filter A2/P3

- · Hand protection Not required.
- · Material of gloves Not required.
- · Penetration time of glove material Not required.
- · Eye/face protection Not required.

#### **SECTION 9: Physical and chemical properties**

- · 9.1 Information on basic physical and chemical properties
- · General Information

Physical state
Colour:
Odour:
Ether-like

(Contd. on page 5)

Printing date 30.05.2022 Version number 116 (replaces version 115) Revision: 30.03.2022

Trade name: PRESTO QUICK START 150 ML

(Contd. of page 4) · Odour threshold: Not determined. · Melting point/freezing point: Undetermined. · Boiling point or initial boiling point and boiling Not applicable, as aerosol. Not applicable. · Flammability · Lower and upper explosion limit · Lower: 1.4 Vol % (109-66-0 pentane) · Upper: 36 Vol % (60-29-7 diethyl ether) Not applicable, as aerosol. · Flash point: 170 °C (338 °F) (60-29-7 diethyl ether) · Ignition temperature: · Decomposition temperature: Not determined. Mixture is non-soluble (in water).  $\cdot pH$ · Viscosity: · Kinematic viscosity *Not determined.* · Dynamic: Not determined. · Solubility · water: Not miscible or difficult to mix. · Partition coefficient n-octanol/water (log value) Not determined. · Vapour pressure at 20 °C (68 °F): 3500 hPa (2625.2 mm Hg) · Density and/or relative density Density at 20 °C (68 °F):  $0.6 \text{ g/cm}^3 (5 \text{ lbs/gal})$ Not determined. · Relative density Not determined. · Vapour density · 9.2 Other information · Appearance: · Form: Aerosol · Important information on protection of health and environment, and on safety. · Explosive properties: May form explosive peroxides. · Solvent content: · Organic solvents: 99.6 % · **VOC** (**EC**)  $630.4 \, g/l$ · VOC-EU% 99.58 % 0.0 % · Solids content: · Change in condition Not applicable. · Evaporation rate · Information with regard to physical hazard classes Void · Explosives · Flammable gases Void · Aerosols Extremely flammable aerosol. Pressurised container: May burst if heated. Void · Oxidising gases · Gases under pressure Void · Flammable liquids Void · Flammable solids Void · Self-reactive substances and mixtures Void · Pyrophoric liquids Void · Pyrophoric solids Void · Self-heating substances and mixtures Void · Substances and mixtures, which emit flammable gases in contact with water Void · Oxidising liquids Void · Oxidising solids Void · Organic peroxides Void · Corrosive to metals Void

Printing date 30.05.2022 Version number 116 (replaces version 115) Revision: 30.03.2022

Trade name: PRESTO QUICK START 150 ML

(Contd. of page 5)

· Desensitised explosives

Void

#### SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

#### SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity
- · LD/LC50 values relevant for classification:

#### 60-29-7 diethyl ether

Oral	LD50	855-2352 mg/kg (rat)
Dermal	LD50	>20000 mg/kg (rab)
Inhalative	LC50 / 4 h	73000 mg/m3 (rat)

#### 109-66-0 pentane

		>5000 mg/kg (rat)
Inhalative	LC50 / 4h	25.3 mg/l (rat)

- · Skin corrosion/irritation No irritant effect.
- · Serious eye damage/irritation No irritating effect.
- · Respiratory or skin sensitisation No sensitising effects known.
- · STOT-single exposure May cause drowsiness or dizziness.
- · 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

#### SECTION 12: Ecological information

· 12.1 Toxicity

	A an	atic	tovici	1111
•	лии	uuu	toxic	uv.

#### 60-29-7 diethyl ether

EC50(24h) 16	mg/l (daphnia magna
--------------	---------------------

EC50 5600 mg/l (Photobacterium phosphoreum)

EC50 / 15 min

LC50 / 48 h 2840 mg/l (Leuciscus idus)

#### 109-66-0 pentane

EC50 / 48 h 9.7 mg/l (daphnia magna)

EC50 / 96 h 4.26 mg/l (fish)

LC50 / 96 h | 4.26 mg/l (fish)

- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.

(Contd. on page 7)

Version number 116 (replaces version 115) Revision: 30.03.2022 Printing date 30.05.2022

Trade name: PRESTO QUICK START 150 ML

(Contd. of page 6)

- · 12.5 Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · **vPvB**: Not applicable.
- · 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- · 12.7 Other adverse effects
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

#### SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation:

Disposal must be made according to official regulations.

Disposal must be made according to official regulations.

SECT	<i>ION 14:</i>	<b>Transport</b>	informat	ion

· 14.1 UN number or ID number

· ADR, IMDG, IATA UN1950

· 14.2 UN proper shipping name

 $\cdot ADR$ 1950 AEROSOLS · IMDG **AEROSOLS** 

 $\cdot$  IATA AEROSOLS, flammable

- · 14.3 Transport hazard class(es)
- $\cdot ADR$



· Class 2 5F Gases.

· Label 2.1

· IMDG, IATA



· Class 2.1 Gases. 2.1

· Label

· 14.4 Packing group

· ADR, IMDG, IATA not regulated

· 14.5 Environmental hazards: Not applicable.

(Contd. on page 8)

Printing date 30.05.2022 Version number 116 (replaces version 115) Revision: 30.03.2022

Trade name: PRESTO QUICK START 150 ML

	(Contd. of pag
14.6 Special precautions for user	Warning: Gases.
Hazard identification number (Kemler code)	
EMS Number:	F- $D$ , $S$ - $U$
Stowage Code	SWI Protected from sources of heat.
o .	SW22 For AEROSOLS with a maximum capacity of 1
	litre: Category A. For AEROSOLS with a capacity
	above 1 litre: Category B. For WASTE AEROSOLS:
	Category C, Clear of living quarters.
Segregation Code	SG69 For AEROSOLS with a maximum capacity of 1
	litre:
	Segregation as for class 9. Stow "separated from" cla
	1 except for division 1.4.
	For AEROSOLS with a capacity above 1 litre:
	Segregation as for the appropriate subdivision of class
	2.
	For WASTE AEROSOLS:
	Segregation as for the appropriate subdivision of class
	2.
14.7 Maritime transport in bulk according to	IMO
instruments	Not applicable.
Transport/Additional information:	
ADR	
Limited quantities (LQ)	IL
Excepted quantities $(\widetilde{EQ})$	Code: E0
· · · · · · · · · · · · · · · · ·	Not permitted as Excepted Quantity
	Code: E0
	Not permitted as Excepted Quantity
	2
Transport category	2
Transport category Tunnel restriction code	$\overline{D}$
	_
Tunnel restriction code IMDG	_
Tunnel restriction code  IMDG  Limited quantities (LQ)	D
Tunnel restriction code IMDG	D  IL Code: E0
Tunnel restriction code  IMDG  Limited quantities (LQ)	D IL
Tunnel restriction code  IMDG  Limited quantities (LQ)	D  IL  Code: E0  Not permitted as Excepted Quantity

### SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P3a FLAMMABLE AEROSOLS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · National regulations:
- · Other regulations, limitations and prohibitive regulations
- · Substances of very high concern (SVHC) according to REACH, Article 57

None of the ingredients is listed.

(Contd. on page 9)

Printing date 30.05.2022 Version number 116 (replaces version 115) Revision: 30.03.2022

Trade name: PRESTO QUICK START 150 ML

(Contd. of page 8)

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

- H220 Extremely flammable gas.
- H224 Extremely flammable liquid and vapour.
- H225 Highly flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H336 May cause drowsiness or dizziness.
- H411 Toxic to aquatic life with long lasting effects.
- EUH019 May form explosive peroxides.

EUH066 Repeated exposure may cause skin dryness or cracking.

- · Department issuing SDS: R&D legislation and regulatory advisor
- · Contact: e-mail: sds-nl@european-aerosols.com
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

 $PBT: \ Persistent, \ Bioaccumulative \ and \ Toxic$ 

SVHC: Substances of Very High Concern

vPvB: very Persistent and very Bioaccumulative

Flam. Gas 1A: Flammable gases - Category 1A

Aerosol 1: Aerosols – Category 1

Press. Gas (Comp.): Gases under pressure - Compressed gas

Flam. Liq. 1: Flammable liquids - Category 1

Flam. Liq. 2: Flammable liquids - Category 2

Acute Tox. 4: Acute toxicity - Category 4

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

\* Data compared to the previous version altered.

GB